

SA性能
40.9mブーム+2m+10mスーパーラフィングジブ

オフセット 作業半径 (m)	5°		15°		30°		45°		60°	
	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)
10.0	79.0	24.0								
11.0	78.1	24.0	79.8	24.0						
12.0	77.1	24.0	78.8	24.0						
14.0	75.1	24.0	76.8	24.0	79.1	24.0				
16.0	73.0	24.0	74.7	24.0	77.0	24.0	78.5	21.4	79.6	19.9
18.0	71.0	24.0	72.7	24.0	74.8	23.3	76.2	20.6	77.1	19.4
20.0	68.9	24.0	70.6	24.0	72.6	22.3	73.9	20.0	74.6	19.1
22.0	66.7	24.0	68.4	23.4	70.2	20.7	71.4	19.0	72.1	18.3
24.0	64.5	23.3	66.0	21.6	67.7	19.3	68.9	17.9	69.4	17.4
26.0	62.0	20.8	63.5	20.0	65.2	18.1	66.3	17.0	66.6	16.6
28.0	59.3	17.9	60.9	18.3	62.6	16.9	63.6	16.1	63.7	15.9
30.0	56.6	15.3	58.2	16.0	59.9	15.9	60.8	15.3		
32.0	53.8	13.1	55.3	13.7	57.0	14.3	57.8	14.5		
34.0	50.9	11.2	52.4	11.7	53.9	12.2	54.5	12.5		
36.0	47.7	9.4	49.2	9.9	50.6	10.3	51.0	10.5		
38.0	44.5	7.9	45.9	8.3	47.2	8.6	47.3	8.7		
40.0	41.0	6.5	42.3	6.8	43.4	7.1				
42.0	37.2	5.2	38.5	5.5	39.3	5.7				
44.0	33.1	4.1	34.1	4.3	34.6	4.4				
46.0	28.3	3.0	29.2	3.2						
掛数		2		2		2		2		2
危険角度(°)		21		21		30		45		60
フック種類		24t		24t		24t		24t		24t
フック質量(t)		0.88		0.88		0.88		0.88		0.88

SA性能
45.5mブーム+2m+10mスーパーラフィングジブ

オフセット 作業半径 (m)	5°		15°		30°		45°		60°	
	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)
11.0	79.4	24.0								
12.0	78.5	24.0								
14.0	76.8	24.0	78.3	24.0						
16.0	75.0	24.0	76.6	24.0	78.6	24.0				
18.0	73.2	24.0	74.8	24.0	76.6	22.1	78.0	19.8	78.8	18.6
20.0	71.4	24.0	72.9	23.4	74.5	20.4	75.8	18.5	76.5	17.5
22.0	69.4	22.2	70.7	20.9	72.4	18.9	73.7	17.3	74.3	16.5
24.0	67.2	19.8	68.6	18.8	70.3	17.5	71.4	16.2	71.9	15.6
26.0	65.0	17.8	66.4	17.0	68.1	16.1	69.1	15.3	69.6	14.8
28.0	62.8	16.1	64.1	15.4	65.7	14.7	66.7	14.2	67.1	14.1
30.0	60.5	14.6	61.8	14.0	63.3	13.4	64.2	13.1	64.5	13.0
32.0	58.1	13.0	59.4	12.8	60.9	12.3	61.7	12.1		
34.0	55.5	11.1	56.9	11.6	58.4	11.3	59.1	11.1		
36.0	52.8	9.3	54.2	9.8	55.7	10.4	56.3	10.3		
38.0	50.0	7.8	51.4	8.2	52.8	8.7	53.3	8.9		
40.0	47.2	6.4	48.5	6.8	49.7	7.2	50.0	7.3		
42.0	44.2	5.1	45.3	5.5	46.4	5.8				
44.0	40.8	4.0	42.1	4.3	43.0	4.5				
46.0	37.4	2.9	38.4	3.2	39.1	3.4				
掛数		2		2		2		2		2
危険角度(°)		32		32		32		45		60
フック種類		24t		24t		24t		24t		24t
フック質量(t)		0.88		0.88		0.88		0.88		0.88

SA性能
50.0mブーム+2m+10mスーパーラフィングジブ

オフセット 作業半径 (m)	5°		15°		30°		45°		60°	
	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)
12.0	79.5	20.0								
14.0	77.9	20.0	79.4	20.0						
16.0	76.4	20.0	77.8	20.0	79.7	20.0				
18.0	74.7	20.0	76.2	20.0	78.0	20.0	79.4	19.6		
20.0	73.2	20.0	74.6	20.0	76.3	19.6	77.5	18.0	78.2	17.1
22.0	71.6	20.0	72.9	19.5	74.5	17.9	75.6	16.6	76.2	15.9
24.0	69.6	18.4	70.9	17.5	72.5	16.4	73.5	15.3	74.0	14.8
26.0	67.7	16.4	68.9	15.7	70.5	14.9	71.5	14.2	72.0	13.8
28.0	65.6	14.7	66.9	14.2	68.4	13.5	69.4	13.1	69.7	12.9
30.0	63.6	13.3	64.8	12.8	66.3	12.3	67.2	12.0	67.4	11.9
32.0	61.5	11.9	62.7	11.6	64.1	11.2	65.0	11.0	65.1	10.9
34.0	59.3	10.7	60.5	10.5	61.8	10.2	62.7	10.1		
36.0	57.0	9.3	58.2	9.6	59.5	9.3	60.3	9.2		
38.0	54.5	7.7	55.8	8.2	57.2	8.5	57.8	8.5		
40.0	52.1	6.3	53.3	6.7	54.6	7.2	55.1	7.4		
42.0	49.4	5.0	50.6	5.4	51.8	5.8	52.1	6.0		
44.0	46.7	3.9	47.9	4.2	49.0	4.6	49.1	4.7		
46.0	43.7	2.8	44.9	3.1	45.8	3.4				
掛数		2		2		2		2		2
危険角度(°)		40		40		40		45		60
フック種類		24t		24t		24t		24t		24t
フック質量(t)		0.88		0.88		0.88		0.88		0.88

SA性能
40.9mブーム+2m+15mスーパーラフィングジブ

オフセット 作業半径 (m)	5°		15°		30°		45°		60°	
	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)
11.0	79.3	12.0								
12.0	78.3	12.0								
14.0	76.5	12.0	78.9	12.0						
16.0	74.6	12.0	77.0	12.0						
18.0	72.7	12.0	75.1	12.0	78.3	12.0				
20.0	70.8	12.0	73.2	12.0	76.3	12.0	78.8	12.0		
22.0	68.8	12.0	71.2	12.0	74.3	12.0	76.7	12.0	78.2	12.0
24.0	66.8	12.0	69.2	12.0	72.2	12.0	74.4	12.0	75.9	12.0
26.0	64.8	12.0	67.1	12.0	70.0	12.0	72.2	12.0	73.4	12.0
28.0	62.7	12.0	64.9	12.0	67.8	12.0	69.9	12.0	70.9	12.0
30.0	60.6	12.0	62.8	12.0	65.5	12.0	67.4	12.0	68.2	11.9
32.0	58.4	12.0	60.5	12.0	63.2	12.0	64.8	11.7	65.4	11.4
34.0	56.1	12.0	58.2	12.0	60.7	11.8	62.2	11.1	62.5	11.0
36.0	53.6	11.3	55.8	12.0	58.1	11.2	59.4	10.6		
38.0	50.9	9.7	53.0	10.4	55.4	10.6	56.4	10.2		
40.0	48.1	8.3	50.2	8.9	52.4	9.6	53.2	9.8		
42.0	45.0	7.0	47.1	7.5	49.1	8.1	49.6	8.3		
44.0	41.9	5.9	43.8	6.3	45.6	6.8				
46.0	38.4	4.8	40.3	5.2	41.8	5.5				
48.0	34.7	3.8	36.4	4.1	37.6	4.4				
50.0	30.5	2.9	32.0	3.2	32.7	3.3				
52.0	25.6	2.1	26.9	2.2						
54.0	19.3	1.3	19.9	1.4						
掛数	1		1		1		1		1	
危険角度(°)	17		17		30		45		60	
フック種類	12t		12t		12t		12t		12t	
フック質量(t)	0.42		0.42		0.42		0.42		0.42	

SA性能
45.5mブーム+2m+15mスーパーラフィングジブ

オフセット 作業半径 (m)	5°		15°		30°		45°		60°	
	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)
14.0	77.8	12.0								
16.0	76.1	12.0	78.4	12.0						
18.0	74.4	12.0	76.6	12.0						
20.0	72.8	12.0	74.9	12.0	77.8	12.0				
22.0	71.0	12.0	73.2	12.0	76.0	12.0	78.2	12.0		
24.0	69.3	12.0	71.4	12.0	74.2	12.0	76.2	12.0	77.6	12.0
26.0	67.5	12.0	69.5	12.0	72.2	12.0	74.2	12.0	75.4	11.7
28.0	65.6	12.0	67.7	12.0	70.3	12.0	72.2	11.7	73.1	11.2
30.0	63.8	12.0	65.8	12.0	68.4	12.0	70.0	11.1	70.9	10.7
32.0	61.8	12.0	63.8	12.0	66.3	11.3	67.7	10.5	68.4	10.2
34.0	59.8	11.7	61.7	11.2	64.1	10.6	65.5	10.0	65.9	9.7
36.0	57.6	10.7	59.5	10.3	61.7	9.9	63.1	9.5	63.3	9.4
38.0	55.3	9.6	57.2	9.5	59.3	9.1	60.6	9.0		
40.0	52.8	8.1	54.8	8.7	56.9	8.5	57.9	8.3		
42.0	50.2	6.9	52.2	7.4	54.2	7.8	55.1	7.7		
44.0	47.5	5.7	49.4	6.2	51.4	6.8	52.1	7.0		
46.0	44.7	4.6	46.5	5.1	48.3	5.6	48.7	5.7		
48.0	41.7	3.6	43.5	4.0	45.0	4.4				
50.0	38.5	2.7	40.2	3.1	41.6	3.4				
52.0	35.0	1.9	36.6	2.2	37.6	2.4				
54.0			32.6	1.4						
掛数	1		1		1		1		1	
危険角度(°)	29		29		30		45		60	
フック種類	12t		12t		12t		12t		12t	
フック質量(t)	0.42		0.42		0.42		0.42		0.42	

SA性能
50.0mブーム+2m+15mスーパーラフィングジブ

オフセット 作業半径 (m)	5°		15°		30°		45°		60°	
	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)
14.0	78.9	12.0								
16.0	77.4	12.0	79.4	12.0						
18.0	76.0	12.0	78.0	12.0						
20.0	74.5	12.0	76.4	12.0	79.1	12.0				
22.0	72.9	12.0	74.9	12.0	77.5	12.0	79.6	12.0		
24.0	71.3	12.0	73.3	12.0	75.9	12.0	77.8	12.0	79.1	12.0
26.0	69.7	12.0	71.7	12.0	74.2	12.0	76.1	12.0	77.1	11.5
28.0	68.1	12.0	70.0	12.0	72.6	12.0	74.3	11.4	75.2	10.9
30.0	66.5	12.0	68.4	12.0	70.7	11.4	72.3	10.6	73.1	10.2
32.0	64.8	11.8	66.6	11.3	68.7	10.6	70.3	9.9	70.9	9.6
34.0	62.8	10.7	64.6	10.3	66.7	9.8	68.2	9.3	68.7	9.1
36.0	60.9	9.7	62.6	9.4	64.7	9.1	66.0	8.7	66.5	8.6
38.0	58.9	8.8	60.6	8.6	62.6	8.3	63.9	8.2	64.1	8.1
40.0	56.7	8.0	58.5	7.9	60.5	7.6	61.5	7.5		
42.0	54.5	6.7	56.3	7.2	58.2	7.0	59.2	6.9		
44.0	52.1	5.5	53.9	6.1	55.8	6.4	56.7	6.4		
46.0	49.7	4.5	51.4	5.0	53.3	5.6	54.1	5.9		
48.0	47.1	3.5	48.9	4.0	50.6	4.5	51.1	4.7		
50.0	44.5	2.6	46.1	3.0	47.7	3.4				
52.0	41.6	1.8	43.2	2.1	44.6	2.5				
54.0			40.1	1.3	41.2	1.6				
掛数	1		1		1		1		1	
危険角度(°)	38		38		38		45		60	
フック種類	12t		12t		12t		12t		12t	
フック質量(t)	0.42		0.42		0.42		0.42		0.42	

SA性能
40.9mブーム+2m+19mスーパーラフィングジブ

オフセット	5°		15°		30°		45°		60°	
作業半径 (m)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)
12.0	79.5	12.0								
14.0	77.8	12.0								
16.0	76.1	12.0	79.0	12.0						
18.0	74.4	12.0	77.3	12.0						
20.0	72.7	12.0	75.5	12.0	79.4	12.0				
22.0	70.9	12.0	73.7	12.0	77.4	12.0				
24.0	69.1	12.0	71.8	12.0	75.5	12.0	78.4	10.4		
26.0	67.2	12.0	69.9	12.0	73.6	11.6	76.2	10.2	78.0	9.1
28.0	65.3	12.0	68.0	12.0	71.5	11.1	74.0	9.9	75.7	9.0
30.0	63.4	12.0	66.0	11.4	69.4	10.7	71.8	9.7	73.2	8.9
32.0	61.3	11.4	63.8	10.9	67.2	10.3	69.5	9.4	70.7	8.8
34.0	59.2	10.7	61.7	10.4	64.9	10.0	67.1	9.2	68.0	8.8
36.0	56.9	10.2	59.5	10.0	62.6	9.6	64.6	9.0	65.3	8.8
38.0	54.7	9.6	57.2	9.6	60.2	9.2	62.0	8.7	62.3	8.6
40.0	52.3	9.1	54.8	9.2	57.6	8.8	59.2	8.4		
42.0	49.6	8.1	52.2	8.8	54.9	8.4	56.2	8.0		
44.0	46.9	6.9	49.5	7.6	52.1	8.0	53.2	7.7		
46.0	44.0	5.9	46.5	6.4	49.0	7.1	49.7	7.3		
48.0	41.0	4.9	43.3	5.4	45.5	5.9				
50.0	37.6	4.0	39.9	4.4	41.8	4.8				
52.0	34.0	3.1	36.1	3.5	37.5	3.8				
54.0	30.0	2.4	31.8	2.6	32.7	2.8				
56.0	25.1	1.6	26.7	1.8						
掛数	1		1		1		1		1	
危険角度(°)	19		19		30		45		60	
フック種類	12t		12t		12t		12t		12t	
フック質量(t)	0.42		0.42		0.42		0.42		0.42	

SA性能
45.5mブーム+2m+19mスーパーラフィングジブ

オフセット	5°		15°		30°		45°		60°	
作業半径 (m)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)
14.0	79.0	12.0								
16.0	77.4	12.0								
18.0	75.9	12.0	78.5	12.0						
20.0	74.3	12.0	77.0	12.0						
22.0	72.8	12.0	75.3	12.0	78.9	12.0				
24.0	71.1	12.0	73.7	12.0	77.1	12.0	79.7	10.6		
26.0	69.5	12.0	72.1	12.0	75.4	11.9	77.9	10.3	79.5	9.2
28.0	67.8	12.0	70.3	12.0	73.5	11.2	76.0	10.1	77.4	9.1
30.0	66.1	12.0	68.7	12.0	71.6	10.5	74.0	9.6	75.3	9.0
32.0	64.4	12.0	66.8	11.2	69.6	9.9	71.9	9.1	73.0	8.6
34.0	62.5	11.2	64.8	10.5	67.6	9.3	69.7	8.6	70.7	8.3
36.0	60.4	10.2	62.7	9.8	65.5	8.8	67.5	8.2	68.3	7.9
38.0	58.4	9.4	60.7	9.0	63.4	8.3	65.2	7.8	65.8	7.6
40.0	56.3	8.6	58.5	8.3	61.2	7.9	62.8	7.4	63.2	7.3
42.0	54.0	7.9	56.3	7.7	58.9	7.4	60.4	7.1		
44.0	51.6	6.7	54.0	7.1	56.5	6.9	57.8	6.8		
46.0	49.2	5.6	51.5	6.3	53.9	6.4	55.0	6.3		
48.0	46.5	4.7	48.8	5.2	51.2	5.9	52.1	5.9		
50.0	43.7	3.7	46.0	4.3	48.2	4.8	48.7	5.0		
52.0	40.9	2.9	43.0	3.4	45.0	3.8				
54.0	37.7	2.1	39.8	2.5	41.5	2.9				
56.0	34.4	1.4	36.3	1.7	37.6	2.0				
掛数	1		1		1		1		1	
危険角度(°)	31		31		31		45		60	
フック種類	12t		12t		12t		12t		12t	
フック質量(t)	0.42		0.42		0.42		0.42		0.42	

SA性能
50.0mブーム+2m+19mスーパーラフィングジブ

オフセット	5°		15°		30°		45°		60°	
作業半径 (m)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)
16.0	78.6	12.0								
18.0	77.2	12.0	79.7	12.0						
20.0	75.8	12.0	78.3	12.0						
22.0	74.4	12.0	76.8	12.0	80.2	12.0				
24.0	73.0	12.0	75.4	12.0	78.6	12.0				
26.0	71.6	12.0	73.9	12.0	77.1	11.9	79.3	10.4		
28.0	70.1	12.0	72.5	12.0	75.3	11.0	77.6	10.0	78.9	9.1
30.0	68.6	12.0	70.8	11.5	73.6	10.2	75.7	9.4	77.0	8.9
32.0	66.9	11.3	69.0	10.6	71.8	9.5	73.8	8.8	75.0	8.4
34.0	65.1	10.3	67.2	9.8	69.9	8.9	71.9	8.3	72.9	7.9
36.0	63.2	9.4	65.4	9.0	68.1	8.3	69.9	7.7	70.8	7.5
38.0	61.4	8.5	63.6	8.3	66.2	7.7	67.9	7.3	68.7	7.1
40.0	59.5	7.8	61.7	7.6	64.2	7.2	65.8	6.8	66.4	6.7
42.0	57.5	7.1	59.6	6.9	62.2	6.7	63.7	6.4	64.0	6.4
44.0	55.5	6.5	57.6	6.3	60.1	6.2	61.4	6.1		
46.0	53.3	5.4	55.5	5.8	57.8	5.7	59.1	5.6		
48.0	51.0	4.4	53.3	5.1	55.5	5.2	56.6	5.2		
50.0	48.6	3.5	50.8	4.1	53.2	4.8	53.9	4.8		
52.0	46.2	2.7	48.3	3.2	50.5	3.8	51.1	4.1		
54.0	43.6	1.9	45.6	2.4	47.6	2.9				
56.0			42.8	1.6	44.6	2.0				
掛数	1		1		1		1		1	
危険角度(°)	39		39		39		45		60	
フック種類	12t		12t		12t		12t		12t	
フック質量(t)	0.42		0.42		0.42		0.42		0.42	

SA性能
40.9mブーム+2m+23mスーパーラフィングジブ

オフセット	5°		15°		30°		45°		60°	
作業半径 (m)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)
14.0	79.1	12.0								
16.0	77.5	12.0								
18.0	75.9	12.0	79.2	12.0						
20.0	74.3	12.0	77.6	12.0						
22.0	72.7	12.0	76.0	12.0	80.2	10.4				
24.0	71.0	12.0	74.2	11.5	78.4	10.1				
26.0	69.3	11.9	72.4	10.9	76.5	9.8	79.9	8.1		
28.0	67.5	11.1	70.5	10.3	74.6	9.4	77.8	7.8		
30.0	65.6	10.4	68.6	9.8	72.6	9.0	75.7	7.6	77.9	6.8
32.0	63.7	9.8	66.7	9.3	70.6	8.7	73.6	7.5	75.5	6.7
34.0	61.7	9.2	64.7	8.8	68.6	8.4	71.4	7.3	73.1	6.7
36.0	59.7	8.7	62.7	8.4	66.5	8.1	69.2	7.1	70.5	6.6
38.0	57.6	8.2	60.6	8.1	64.3	7.8	66.8	7.0	67.9	6.6
40.0	55.5	7.8	58.5	7.7	62.0	7.5	64.3	6.9	65.1	6.5
42.0	53.3	7.4	56.2	7.4	59.7	7.3	61.8	6.8	62.2	6.5
44.0	51.0	7.0	53.9	7.1	57.3	7.1	59.1	6.7		
46.0	48.6	6.7	51.5	6.9	54.6	6.8	56.2	6.5		
48.0	45.9	5.8	48.9	6.5	51.9	6.5	53.0	6.3		
50.0	43.1	4.9	46.0	5.5	48.9	6.2	49.6	6.1		
52.0	40.2	4.1	42.9	4.6	45.5	5.2				
54.0	36.9	3.3	39.5	3.7	41.8	4.2				
56.0	33.4	2.6	35.9	2.9	37.6	3.3				
58.0	29.4	1.9	31.7	2.2	32.7	2.4				
60.0	24.9	1.3	26.7	1.5						
掛数	1		1		1		1		1	
危険角度(°)	21		21		30		45		60	
フック種類	12t		12t		12t		12t		12t	
フック質量(t)	0.42		0.42		0.42		0.42		0.42	

SA性能
45.5mブーム+2m+23mスーパーラフィングジブ

オフセット	5°		15°		30°		45°		60°	
作業半径 (m)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)
16.0	78.7	12.0								
18.0	77.2	12.0								
20.0	75.8	12.0	78.9	12.0						
22.0	74.3	12.0	77.4	12.0						
24.0	72.9	12.0	75.9	12.0	79.7	10.2				
26.0	71.4	12.0	74.2	11.3	78.0	9.9				
28.0	69.8	11.8	72.5	10.7	76.3	9.6	79.2	7.9		
30.0	68.1	11.1	70.9	10.2	74.6	9.3	77.4	7.7	79.3	6.9
32.0	66.4	10.4	69.2	9.7	72.7	8.9	75.5	7.6	77.2	6.8
34.0	64.6	9.8	67.4	9.3	70.9	8.4	73.5	7.4	75.1	6.7
36.0	62.9	9.3	65.6	8.9	69.0	7.9	71.6	7.2	72.9	6.6
38.0	61.0	8.8	63.8	8.4	67.0	7.5	69.5	6.9	70.6	6.6
40.0	59.1	8.3	61.7	7.8	65.0	7.1	67.3	6.6	68.3	6.3
42.0	57.1	7.6	59.8	7.4	63.0	6.7	65.0	6.3	65.7	6.1
44.0	55.1	7.0	57.7	6.8	60.7	6.3	62.7	6.0	63.1	5.9
46.0	52.9	6.5	55.5	6.3	58.5	6.0	60.2	5.7		
48.0	50.6	5.5	53.2	5.8	56.2	5.7	57.7	5.5		
50.0	48.2	4.6	50.9	5.3	53.7	5.3	54.9	5.2		
52.0	45.6	3.8	48.3	4.4	51.0	4.9	52.0	4.9		
54.0	42.9	3.0	45.6	3.6	48.2	4.2	48.7	4.4		
56.0	40.2	2.3	42.7	2.8	44.9	3.3				
58.0	37.1	1.6	39.5	2.1	41.5	2.5				
60.0			36.1	1.4	37.6	1.7				
掛数	1		1		1		1		1	
危険角度(°)	33		33		33		45		60	
フック種類	12t		12t		12t		12t		12t	
フック質量(t)	0.42		0.42		0.42		0.42		0.42	

SA性能
50.0mブーム+2m+23mスーパーラフィングジブ

オフセット	5°		15°		30°		45°		60°	
作業半径 (m)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)
16.0	79.6	11.0								
18.0	78.3	11.0								
20.0	77.0	11.0	79.8	11.0						
22.0	75.7	11.0	78.5	11.0						
24.0	74.4	11.0	77.2	11.0						
26.0	73.0	11.0	75.8	11.0	79.3	10.1				
28.0	71.7	11.0	74.4	11.0	77.8	9.8				
30.0	70.3	11.0	72.9	10.6	76.3	9.4	78.8	7.8		
32.0	68.8	10.9	71.3	9.8	74.6	8.7	77.1	7.7	78.7	6.8
34.0	67.2	10.0	69.7	9.1	72.9	8.1	75.4	7.5	76.9	6.7
36.0	65.5	9.1	67.9	8.4	71.1	7.6	73.5	7.0	74.9	6.7
38.0	63.7	8.3	66.2	7.8	69.4	7.1	71.6	6.6	72.8	6.4
40.0	62.0	7.6	64.4	7.2	67.5	6.6	69.7	6.2	70.7	6.0
42.0	60.1	6.9	62.7	6.7	65.6	6.2	67.7	5.8	68.5	5.7
44.0	58.3	6.3	60.8	6.2	63.7	5.8	65.7	5.5	66.3	5.4
46.0	56.5	5.8	58.8	5.7	61.7	5.4	63.5	5.2	63.9	5.1
48.0	54.4	5.3	56.9	5.2	59.7	5.1	61.3	4.9		
50.0	52.3	4.4	54.9	4.8	57.6	4.7	59.0	4.6		
52.0	50.1	3.6	52.7	4.2	55.3	4.3	56.6	4.3		
54.0	47.8	2.8	50.3	3.4	53.0	4.0	53.9	4.0		
56.0	45.3	2.1	47.8	2.6	50.3	3.3	51.1	3.6		
58.0	42.8	1.4	45.2	1.9	47.5	2.4				
60.0					44.6	1.7				
掛数	1		1		1		1		1	
危険角度(°)	40		41		41		45		60	
フック種類	12t		12t		12t		12t		12t	
フック質量(t)	0.42		0.42		0.42		0.42		0.42	

SA性能
40.9mブーム+2m+27mスーパーラフィングジブ

オフセット	5°		15°		30°		45°		60°	
作業半径 (m)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)
14.0	80.3	12.0								
16.0	78.9	12.0								
18.0	77.4	12.0								
20.0	75.9	12.0	79.5	11.2						
22.0	74.4	12.0	77.9	10.7						
24.0	72.8	11.4	76.2	10.2						
26.0	71.1	10.6	74.5	9.6	79.2	7.9				
28.0	69.4	9.9	72.8	9.1	77.4	7.6				
30.0	67.7	9.2	71.1	8.6	75.7	7.4	79.4	6.3		
32.0	65.9	8.6	69.3	8.1	73.8	7.2	77.4	6.1	80.0	5.4
34.0	64.1	8.1	67.5	7.7	71.9	7.0	75.4	6.0	77.7	5.3
36.0	62.2	7.6	65.6	7.4	70.0	6.8	73.3	5.8	75.4	5.2
38.0	60.3	7.2	63.7	7.0	68.0	6.6	71.1	5.7	73.0	5.2
40.0	58.4	6.8	61.8	6.7	65.9	6.4	68.9	5.5	70.4	5.1
42.0	56.4	6.4	59.7	6.4	63.8	6.2	66.6	5.4	67.9	5.1
44.0	54.4	6.1	57.6	6.1	61.6	6.0	64.2	5.3	65.1	5.1
46.0	52.2	5.8	55.4	5.9	59.4	5.8	61.7	5.3	62.1	5.1
48.0	49.9	5.5	53.2	5.7	56.9	5.7	59.0	5.2		
50.0	47.7	5.2	50.9	5.5	54.4	5.5	56.1	5.1		
52.0	45.2	4.9	48.4	5.3	51.7	5.3	53.0	5.1		
54.0	42.4	4.1	45.6	4.7	48.7	5.1	49.6	5.0		
56.0	39.5	3.4	42.6	3.9	45.5	4.5				
58.0	36.3	2.7	39.3	3.2	41.8	3.7				
60.0	32.9	2.1	35.7	2.5	37.7	2.9				
62.0	29.1	1.5	31.5	1.8	32.6	2.1				
掛数	1		1		1		1		1	
危険角度(°)	23		23		30		45		60	
フック種類	12t		12t		12t		12t		12t	
フック質量(t)	0.42		0.42		0.42		0.42		0.42	

SA性能
45.5mブーム+2m+27mスーパーラフィングジブ

オフセット	5°		15°		30°		45°		60°	
作業半径 (m)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)
16.0	79.8	11.0								
18.0	78.4	11.0								
20.0	77.1	11.0	80.5	11.0						
22.0	75.7	11.0	79.2	10.9						
24.0	74.3	11.0	77.6	10.4						
26.0	73.0	11.0	76.2	10.0	80.3	8.0				
28.0	71.5	10.5	74.6	9.4	78.8	7.8				
30.0	69.9	9.8	73.0	8.9	77.1	7.5				
32.0	68.3	9.2	71.4	8.5	75.5	7.3	78.8	6.2		
34.0	66.6	8.6	69.8	8.1	73.8	7.1	76.9	6.0	79.2	5.3
36.0	65.0	8.1	68.1	7.7	72.1	7.0	75.2	5.9	77.1	5.3
38.0	63.3	7.7	66.4	7.4	70.3	6.8	73.3	5.8	75.0	5.2
40.0	61.5	7.3	64.6	7.0	68.5	6.4	71.3	5.6	72.8	5.1
42.0	59.7	6.9	62.8	6.7	66.5	6.1	69.3	5.5	70.6	5.1
44.0	57.9	6.5	60.9	6.4	64.6	5.8	67.2	5.4	68.1	5.1
46.0	56.0	6.2	59.0	6.0	62.6	5.5	64.9	5.1	65.7	5.0
48.0	54.1	5.8	57.1	5.7	60.4	5.2	62.7	4.9	63.0	4.8
50.0	52.0	5.4	54.9	5.2	58.3	4.9	60.2	4.7		
52.0	49.8	4.6	52.7	4.9	56.0	4.7	57.6	4.5		
54.0	47.4	3.8	50.5	4.5	53.6	4.4	55.0	4.3		
56.0	44.9	3.1	47.9	3.7	51.0	4.1	51.9	4.1		
58.0	42.3	2.4	45.2	3.0	48.1	3.6	48.7	3.8		
60.0	39.5	1.8	42.3	2.3	45.0	2.8				
62.0			39.3	1.6	41.5	2.1				
64.0					37.6	1.4				
掛数	1		1		1		1		1	
危険角度(°)	34		35		35		45		60	
フック種類	12t		12t		12t		12t		12t	
フック質量(t)	0.42		0.42		0.42		0.42		0.42	

SA性能
50.0mブーム+2m+27mスーパーラフィングジブ

オフセット	5°		15°		30°		45°		60°	
作業半径 (m)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)
18.0	79.1	9.0								
20.0	77.9	9.0								
22.0	76.7	9.0	79.9	9.0						
24.0	75.4	9.0	78.6	9.0						
26.0	74.1	9.0	77.3	9.0						
28.0	72.9	9.0	76.0	9.0	80.0	7.9				
30.0	71.6	9.0	74.7	9.0	78.5	7.6				
32.0	70.3	9.0	73.3	8.8	77.0	7.4	80.1	6.3		
34.0	68.9	9.0	71.8	8.4	75.5	7.3	78.4	6.1		
36.0	67.4	8.6	70.3	7.9	73.9	7.0	76.8	6.0	78.6	5.3
38.0	65.9	8.0	68.6	7.3	72.3	6.6	75.0	5.8	76.7	5.2
40.0	64.3	7.4	67.0	6.8	70.6	6.2	73.3	5.7	74.8	5.2
42.0	62.5	6.8	65.3	6.3	68.9	5.8	71.5	5.4	72.8	5.1
44.0	60.9	6.2	63.6	5.9	67.1	5.4	69.5	5.1	70.7	4.9
46.0	59.1	5.7	61.9	5.5	65.3	5.1	67.6	4.8	68.5	4.7
48.0	57.3	5.2	60.0	5.1	63.4	4.7	65.6	4.5	66.2	4.4
50.0	55.5	4.8	58.2	4.7	61.4	4.4	63.4	4.2	63.8	4.2
52.0	53.6	4.3	56.2	4.3	59.5	4.2	61.3	4.0		
54.0	51.5	3.5	54.3	3.9	57.3	3.9	59.0	3.8		
56.0	49.3	2.8	52.2	3.5	55.2	3.6	56.5	3.6		
58.0	47.0	2.2	49.8	2.8	52.8	3.3	53.9	3.3		
60.0	44.6	1.5	47.4	2.1	50.3	2.8	51.1	3.0		
62.0			44.9	1.5	47.5	2.0				
64.0					44.5	1.3				
掛数	1		1		1		1		1	
危険角度(°)	42		42		42		45		60	
フック種類	12t		12t		12t		12t		12t	
フック質量(t)	0.42		0.42		0.42		0.42		0.42	

SA性能
40.9mブーム+2m+31mスーパーラフィングジブ

オフセット	5°		15°		30°		45°		60°	
作業半径 (m)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)
16.0	79.7	9.0								
18.0	78.3	9.0								
20.0	76.9	9.0								
22.0	75.5	9.0	79.6	9.0						
24.0	74.1	9.0	78.1	8.7						
26.0	72.7	9.0	76.5	8.3						
28.0	71.2	8.9	74.9	8.0	80.0	6.4				
30.0	69.6	8.3	73.3	7.6	78.4	6.2				
32.0	67.9	7.8	71.7	7.3	76.7	6.1				
34.0	66.2	7.3	70.0	6.9	74.9	5.9	79.0	4.9		
36.0	64.5	6.8	68.3	6.6	73.2	5.7	77.0	4.8		
38.0	62.8	6.4	66.4	6.2	71.2	5.5	75.1	4.7	77.7	4.2
40.0	61.0	6.1	64.6	5.9	69.4	5.3	73.1	4.6	75.4	4.2
42.0	59.1	5.7	62.8	5.7	67.5	5.1	70.9	4.5	73.0	4.1
44.0	57.2	5.4	60.9	5.4	65.5	5.0	68.8	4.4	70.5	4.1
46.0	55.3	5.1	59.0	5.2	63.4	4.8	66.5	4.3	67.8	4.0
48.0	53.4	4.9	56.9	5.0	61.2	4.7	64.0	4.2	64.9	4.0
50.0	51.2	4.6	54.8	4.8	59.0	4.6	61.6	4.2	62.0	4.0
52.0	49.1	4.4	52.7	4.6	56.6	4.5	58.9	4.1		
54.0	46.9	4.2	50.3	4.4	54.2	4.4	56.1	4.1		
56.0	44.5	4.0	47.9	4.3	51.6	4.3	52.9	4.0		
58.0	41.9	3.5	45.3	4.1	48.7	4.2	49.5	4.0		
60.0	39.0	2.8	42.4	3.4	45.5	4.0				
62.0	35.9	2.2	39.1	2.7	41.9	3.2				
64.0	32.5	1.7	35.5	2.1	37.6	2.5				
66.0			31.5	1.5	32.6	1.7				
72.0										
掛数	1		1		1		1		1	
危険角度(°)	26		26		30		45		60	
フック種類	12t		12t		12t		12t		12t	
フック質量(t)	0.42		0.42		0.42		0.42		0.42	

SA性能
45.5mブーム+2m+31mスーパーラフィングジブ

オフセット	5°		15°		30°		45°		60°	
作業半径 (m)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)
18.0	79.3	9.0								
20.0	78.0	9.0								
22.0	76.8	9.0	80.6	9.0						
24.0	75.5	9.0	79.3	9.0						
26.0	74.2	9.0	77.8	8.5						
28.0	72.9	9.0	76.4	8.2						
30.0	71.5	8.8	74.9	7.8	79.6	6.3				
32.0	70.0	8.3	73.5	7.5	78.0	6.1				
34.0	68.5	7.7	72.0	7.2	76.4	6.0	80.2	5.0		
36.0	66.9	7.3	70.4	6.8	74.9	5.8	78.5	4.9		
38.0	65.3	6.9	68.8	6.5	73.2	5.6	76.6	4.7	79.1	4.2
40.0	63.7	6.5	67.1	6.2	71.5	5.4	74.8	4.6	77.1	4.2
42.0	62.1	6.1	65.5	6.0	69.8	5.3	72.9	4.5	75.0	4.1
44.0	60.4	5.8	63.8	5.7	68.0	5.1	71.1	4.5	72.7	4.1
46.0	58.7	5.5	62.0	5.5	66.2	5.0	69.1	4.4	70.5	4.0
48.0	56.9	5.2	60.2	5.2	64.3	4.8	67.0	4.3	68.1	4.0
50.0	55.1	5.0	58.4	5.0	62.2	4.5	64.9	4.2	65.6	4.0
52.0	53.2	4.7	56.5	4.7	60.2	4.3	62.6	4.1	62.9	4.0
54.0	51.3	4.5	54.4	4.4	58.0	4.1	60.2	3.9		
56.0	49.0	3.8	52.3	4.1	55.9	3.9	57.6	3.7		
58.0	46.7	3.1	50.1	3.8	53.4	3.7	54.9	3.6		
60.0	44.2	2.5	47.5	3.1	50.9	3.5	51.9	3.4		
62.0	41.7	1.9	44.9	2.5	48.1	3.2	48.6	3.2		
64.0	39.0	1.4	42.1	1.9	45.0	2.4				
66.0			39.1	1.3	41.5	1.8				
掛数	1		1		1		1		1	
危険角度(°)	36		36		36		45		60	
フック種類	12t		12t		12t		12t		12t	
フック質量(t)	0.42		0.42		0.42		0.42		0.42	

SA性能
50.0mブーム+2m+31mスーパーラフィングジブ

オフセット	5°		15°		30°		45°		60°	
作業半径 (m)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)
18.0	80.0	8.0								
20.0	78.8	8.0								
22.0	77.7	8.0								
24.0	76.6	8.0	80.1	8.0						
26.0	75.4	8.0	78.9	8.0						
28.0	74.1	8.0	77.7	8.0						
30.0	72.9	8.0	76.5	8.0	80.6	6.4				
32.0	71.7	8.0	75.0	7.7	79.3	6.2				
34.0	70.5	8.0	73.7	7.4	77.8	6.1				
36.0	69.2	7.7	72.3	7.1	76.4	5.9	79.7	4.9		
38.0	67.7	7.3	70.9	6.8	74.8	5.7	78.1	4.8		
40.0	66.2	6.9	69.4	6.4	73.4	5.5	76.5	4.7	78.6	4.2
42.0	64.7	6.5	67.8	6.0	71.8	5.4	74.8	4.6	76.7	4.1
44.0	63.2	6.0	66.3	5.6	70.2	5.1	73.1	4.5	74.8	4.1
46.0	61.6	5.6	64.6	5.2	68.4	4.7	71.3	4.4	72.8	4.1
48.0	59.9	5.1	62.9	4.8	66.7	4.4	69.4	4.2	70.7	4.0
50.0	58.2	4.7	61.3	4.5	64.9	4.2	67.5	4.0	68.5	3.9
52.0	56.4	4.3	59.4	4.2	63.1	3.9	65.5	3.7	66.1	3.7
54.0	54.7	3.9	57.7	3.9	61.2	3.7	63.4	3.5		
56.0	52.8	3.5	55.8	3.6	59.3	3.4	61.2	3.3		
58.0	50.7	2.8	53.9	3.3	57.1	3.2	58.9	3.1		
60.0	48.5	2.2	51.8	2.9	55.1	3.0	56.5	2.9		
62.0	46.3	1.6	49.4	2.3	52.7	2.7	53.9	2.8		
64.0			47.1	1.6	50.2	2.4	51.1	2.5		
66.0					47.5	1.7				
掛数	1		1		1		1		1	
危険角度(°)	43		43		43		45		60	
フック種類	12t		12t		12t		12t		12t	
フック質量(t)	0.42		0.42		0.42		0.42		0.42	

SB性能

40.9mブーム+2m+10mスーパーラフィングジブ

オフセット 作業半径 (m)	5°		15°		30°		45°		60°	
	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)
10.0	79.0	24.0								
11.0	78.1	24.0	79.8	24.0						
12.0	77.1	24.0	78.8	24.0						
14.0	75.1	24.0	76.8	24.0	79.1	24.0				
16.0	73.0	24.0	74.7	24.0	77.0	24.0	78.5	21.4	79.6	19.9
18.0	71.0	24.0	72.7	24.0	74.8	23.3	76.2	20.6	77.1	19.4
20.0	68.9	24.0	70.6	24.0	72.6	22.3	73.9	20.0	74.6	19.1
22.0	66.7	23.6	68.4	23.4	70.2	20.7	71.4	19.0	72.1	18.3
24.0	64.1	19.9	65.9	20.8	67.7	19.3	68.9	17.9	69.4	17.4
26.0	61.6	16.8	63.2	17.6	65.2	18.1	66.3	17.0	66.6	16.6
28.0	58.9	14.2	60.5	14.9	62.4	15.8	63.6	16.1	63.7	15.9
30.0	56.2	11.9	57.8	12.5	59.6	13.3	60.6	13.8		
32.0	53.4	9.9	54.9	10.4	56.6	11.1	57.4	11.5		
34.0	50.5	8.1	52.0	8.6	53.5	9.2	54.2	9.4		
36.0	47.3	6.5	48.8	7.0	50.3	7.5	50.7	7.6		
38.0	44.1	5.1	45.5	5.5	46.8	5.9				
40.0	40.7	3.9	41.9	4.2	43.1	4.5				
42.0	36.8	2.8	38.1	3.0	38.9	3.2				
掛数	2		2		2		2		2	
危険角度(°)	33		33		33		45		60	
フック種類	24t		24t		24t		24t		24t	
フック質量(t)	0.88		0.88		0.88		0.88		0.88	

SB性能

45.5mブーム+2m+10mスーパーラフィングジブ

オフセット 作業半径 (m)	5°		15°		30°		45°		60°	
	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)
11.0	79.4	24.0								
12.0	78.5	24.0								
14.0	76.8	24.0	78.3	24.0						
16.0	75.0	24.0	76.6	24.0	78.6	24.0				
18.0	73.2	24.0	74.8	24.0	76.6	22.1	78.0	19.8	78.8	18.6
20.0	71.4	24.0	72.9	23.4	74.5	20.4	75.8	18.5	76.5	17.5
22.0	69.4	22.2	70.7	20.9	72.4	18.9	73.7	17.3	74.3	16.5
24.0	67.2	19.8	68.6	18.8	70.3	17.5	71.4	16.2	71.9	15.6
26.0	64.9	16.7	66.4	17.0	68.1	16.1	69.1	15.3	69.6	14.8
28.0	62.5	14.1	64.1	14.8	65.7	14.7	66.7	14.2	67.1	14.1
30.0	60.1	11.8	61.6	12.5	63.3	13.3	64.2	13.1	64.5	13.0
32.0	57.6	9.8	59.0	10.4	60.7	11.1	61.6	11.6		
34.0	55.1	8.0	56.5	8.6	58.0	9.2	58.9	9.6		
36.0	52.3	6.5	53.7	6.9	55.3	7.5	55.9	7.8		
38.0	49.6	5.1	51.0	5.5	52.3	6.0	52.8	6.2		
40.0	46.7	3.8	48.0	4.2	49.3	4.6	49.6	4.7		
42.0	43.7	2.7	44.9	3.0	46.0	3.3				
掛数	2		2		2		2		2	
危険角度(°)	41		41		41		45		60	
フック種類	24t		24t		24t		24t		24t	
フック質量(t)	0.88		0.88		0.88		0.88		0.88	

SB性能

50.0mブーム+2m+10mスーパーラフィングジブ

オフセット 作業半径 (m)	5°		15°		30°		45°		60°	
	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)
12.0	79.5	20.0								
14.0	77.9	20.0	79.4	20.0						
16.0	76.4	20.0	77.8	20.0						
18.0	74.7	20.0	76.2	20.0	79.7	20.0				
20.0	73.2	20.0	74.6	20.0	78.0	20.0	79.4	19.6		
22.0	71.6	20.0	72.9	19.5	76.3	19.6	77.5	18.0	78.2	17.1
24.0	69.6	18.4	70.9	17.5	74.5	17.9	75.6	16.6	76.2	15.9
26.0	67.7	16.4	68.9	15.7	72.5	16.4	73.5	15.3	74.0	14.8
28.0	65.5	14.0	66.9	14.2	70.5	14.9	71.5	14.2	72.0	13.8
30.0	63.4	11.7	64.7	12.4	68.4	13.5	69.4	13.1	69.7	12.9
32.0	61.1	9.7	62.4	10.4	66.3	12.3	67.2	12.0	67.4	11.9
34.0	58.8	7.9	60.2	8.5	64.0	11.1	65.0	11.0	65.1	10.9
36.0	56.4	6.4	57.7	6.9	61.7	9.2	62.6	9.7		
38.0	54.0	5.0	55.3	5.4	59.2	7.5	60.0	7.9		
40.0	51.5	3.7	52.7	4.1	56.7	6.0	57.3	6.3		
42.0			50.1	3.0	54.1	4.6	54.6	4.8		
					51.3	3.4	51.6	3.5		
掛数	2		2		2		2		2	
危険角度(°)	47		47		47		47		60	
フック種類	24t		24t		24t		24t		24t	
フック質量(t)	0.88		0.88		0.88		0.88		0.88	

SB性能

40.9mブーム+2m+15mスーパーラフィングジブ

オフセット 作業半径 (m)	5°		15°		30°		45°		60°	
	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)
11.0	79.3	12.0								
12.0	78.3	12.0								
14.0	76.5	12.0	78.9	12.0						
16.0	74.6	12.0	77.0	12.0						
18.0	72.7	12.0	75.1	12.0	78.3	12.0				
20.0	70.8	12.0	73.2	12.0	76.3	12.0	78.8	12.0		
22.0	68.8	12.0	71.2	12.0	74.3	12.0	76.7	12.0	78.2	12.0
24.0	66.8	12.0	69.2	12.0	72.2	12.0	74.4	12.0	75.9	12.0
26.0	64.8	12.0	67.1	12.0	70.0	12.0	72.2	12.0	73.4	12.0
28.0	62.7	12.0	64.9	12.0	67.8	12.0	69.9	12.0	70.9	12.0
30.0	60.6	12.0	62.8	12.0	65.5	12.0	67.4	12.0	68.2	11.9
32.0	58.4	11.8	60.5	12.0	63.2	12.0	64.8	11.7	65.4	11.4
34.0	55.8	10.0	58.0	10.8	60.7	11.8	62.2	11.1	62.5	11.0
36.0	53.2	8.4	55.4	9.2	57.9	10.0	59.4	10.6		
38.0	50.5	7.0	52.6	7.7	55.0	8.4	56.2	8.9		
40.0	47.6	5.7	49.7	6.3	52.0	7.0	52.9	7.3		
42.0	44.6	4.6	46.7	5.1	48.7	5.6	49.3	5.9		
44.0	41.4	3.5	43.4	3.9	45.2	4.4				
46.0	38.0	2.5	39.9	2.9	41.4	3.3				
48.0	34.3	1.6	36.0	2.0	37.2	2.2				
掛数		1		1		1		1		1
危険角度(°)		30		30		30		45		60
フック種類		12t		12t		12t		12t		12t
フック質量(t)		0.42		0.42		0.42		0.42		0.42

SB性能

45.5mブーム+2m+15mスーパーラフィングジブ

オフセット 作業半径 (m)	5°		15°		30°		45°		60°	
	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)
14.0	77.8	12.0								
16.0	76.1	12.0	78.4	12.0						
18.0	74.4	12.0	76.6	12.0						
20.0	72.8	12.0	74.9	12.0	77.8	12.0				
22.0	71.0	12.0	73.2	12.0	76.0	12.0	78.2	12.0		
24.0	69.3	12.0	71.4	12.0	74.2	12.0	76.2	12.0	77.6	12.0
26.0	67.5	12.0	69.5	12.0	72.2	12.0	74.2	12.0	75.4	11.7
28.0	65.6	12.0	67.7	12.0	70.3	12.0	72.2	11.7	73.1	11.2
30.0	63.8	12.0	65.8	12.0	68.4	12.0	70.0	11.1	70.9	10.7
32.0	61.8	11.7	63.8	12.0	66.3	11.3	67.7	10.5	68.4	10.2
34.0	59.5	9.9	61.7	10.7	64.1	10.6	65.5	10.0	65.9	9.7
36.0	57.1	8.3	59.3	9.0	61.7	9.9	63.1	9.5	63.3	9.4
38.0	54.8	6.8	56.8	7.5	59.2	8.4	60.5	9.0		
40.0	52.3	5.5	54.3	6.2	56.6	7.0	57.7	7.4		
42.0	49.7	4.4	51.7	5.0	53.8	5.6	54.8	6.0		
44.0	47.0	3.3	48.9	3.8	50.9	4.4	51.7	4.7		
46.0	44.2	2.4	46.0	2.8	47.8	3.3	48.3	3.5		
48.0	41.2	1.5	43.0	1.9	44.6	2.3				
50.0					41.1	1.3				
掛数		1		1		1		1		1
危険角度(°)		30		30		30		45		60
フック種類		12t		12t		12t		12t		12t
フック質量(t)		0.42		0.42		0.42		0.42		0.42

SB性能

50.0mブーム+2m+15mスーパーラフィングジブ

オフセット 作業半径 (m)	5°		15°		30°		45°		60°	
	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)
14.0	78.9	12.0								
16.0	77.4	12.0	79.4	12.0						
18.0	76.0	12.0	78.0	12.0						
20.0	74.5	12.0	76.4	12.0	79.1	12.0				
22.0	72.9	12.0	74.9	12.0	77.5	12.0	79.6	12.0		
24.0	71.3	12.0	73.3	12.0	75.9	12.0	77.8	12.0	79.1	12.0
26.0	69.7	12.0	71.7	12.0	74.2	12.0	76.1	12.0	77.1	11.5
28.0	68.1	12.0	70.0	12.0	72.6	12.0	74.3	11.4	75.2	10.9
30.0	66.5	12.0	68.4	12.0	70.7	11.4	72.3	10.6	73.1	10.2
32.0	64.7	11.5	66.6	11.3	68.7	10.6	70.3	9.9	70.9	9.6
34.0	62.6	9.7	64.6	10.3	66.7	9.8	68.2	9.3	68.7	9.1
36.0	60.6	8.1	62.5	8.9	64.7	9.1	66.0	8.7	66.5	8.6
38.0	58.4	6.7	60.3	7.4	62.6	8.3	63.9	8.2	64.1	8.1
40.0	56.1	5.4	58.1	6.1	60.3	6.9	61.5	7.5		
42.0	53.9	4.2	55.8	4.9	57.8	5.6	59.0	6.1		
44.0	51.5	3.2	53.3	3.7	55.4	4.4	56.3	4.8		
46.0	49.1	2.2	50.8	2.7	52.8	3.3	53.5	3.6		
48.0			48.3	1.8	50.0	2.3	50.5	2.5		
50.0					47.1	1.4				
掛数		1		1		1		1		1
危険角度(°)		45		45		45		45		60
フック種類		12t		12t		12t		12t		12t
フック質量(t)		0.42		0.42		0.42		0.42		0.42

SB性能

40.9mブーム+2m+19mスーパーラフィングジブ

オフセット 作業半径 (m)	5°		15°		30°		45°		60°	
	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)
12.0	79.5	12.0								
14.0	77.8	12.0								
16.0	76.1	12.0	79.0	12.0						
18.0	74.4	12.0	77.3	12.0						
20.0	72.7	12.0	75.5	12.0	79.4	12.0				
22.0	70.9	12.0	73.7	12.0	77.4	12.0				
24.0	69.1	12.0	71.8	12.0	75.5	12.0	78.4	10.4		
26.0	67.2	12.0	69.9	12.0	73.6	11.6	76.2	10.2	78.0	9.1
28.0	65.3	12.0	68.0	12.0	71.5	11.1	74.0	9.9	75.7	9.0
30.0	63.4	12.0	66.0	11.4	69.4	10.7	71.8	9.7	73.2	8.9
32.0	61.3	11.4	63.8	10.9	67.2	10.3	69.5	9.4	70.7	8.8
34.0	59.2	10.7	61.7	10.4	64.9	10.0	67.1	9.2	68.0	8.8
36.0	56.8	9.5	59.5	10.0	62.6	9.6	64.6	9.0	65.3	8.8
38.0	54.4	8.1	57.0	9.0	60.2	9.2	62.0	8.7	62.3	8.6
40.0	51.8	6.8	54.5	7.6	57.6	8.6	59.2	8.4		
42.0	49.2	5.6	51.8	6.3	54.7	7.2	56.2	7.7		
44.0	46.4	4.6	49.0	5.2	51.7	6.0	52.9	6.4		
46.0	43.5	3.6	46.0	4.2	48.6	4.8	49.3	5.1		
48.0	40.5	2.7	42.8	3.2	45.1	3.7				
50.0	37.1	1.9	39.5	2.3	41.4	2.7				
52.0			35.7	1.5	37.2	1.8				
掛数	1		1		1		1		1	
危険角度(°)	32		32		32		45		60	
フック種類	12t		0.42		0.42		0.42		0.42	
フック質量(t)	0.42				1		1		1	

SB性能

45.5mブーム+2m+19mスーパーラフィングジブ

オフセット 作業半径 (m)	5°		15°		30°		45°		60°	
	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)
14.0	79.0	12.0								
16.0	77.4	12.0								
18.0	75.9	12.0	78.5	12.0						
20.0	74.3	12.0	77.0	12.0						
22.0	72.8	12.0	75.3	12.0	78.9	12.0				
24.0	71.1	12.0	73.7	12.0	77.1	12.0	79.7	10.6		
26.0	69.5	12.0	72.1	12.0	75.4	11.9	77.9	10.3	79.5	9.2
28.0	67.8	12.0	70.3	12.0	73.5	11.2	76.0	10.1	77.4	9.1
30.0	66.1	12.0	68.7	12.0	71.6	10.5	74.0	9.6	75.3	9.0
32.0	64.4	12.0	66.8	11.2	69.6	9.9	71.9	9.1	73.0	8.6
34.0	62.4	10.9	64.8	10.5	67.6	9.3	69.7	8.6	70.7	8.3
36.0	60.3	9.3	62.7	9.8	65.5	8.8	67.5	8.2	68.3	7.9
38.0	58.1	7.9	60.6	8.8	63.4	8.3	65.2	7.8	65.8	7.6
40.0	55.8	6.6	58.4	7.4	61.2	7.9	62.8	7.4	63.2	7.3
42.0	53.4	5.4	56.0	6.2	58.8	7.1	60.4	7.1		
44.0	51.1	4.4	53.5	5.0	56.2	5.9	57.7	6.4		
46.0	48.6	3.4	50.9	4.0	53.5	4.8	54.8	5.2		
48.0	45.9	2.5	48.2	3.1	50.7	3.7	51.7	4.0		
50.0	43.2	1.7	45.5	2.2	47.7	2.7	48.3	3.0		
52.0			42.5	1.4	44.5	1.8				
掛数	1		1		1		1		1	
危険角度(°)	40		40		40		45		60	
フック種類	12t		12t		12t		12t		12t	
フック質量(t)	0.42		0.42		0.42		0.42		0.42	

SB性能

50.0mブーム+2m+19mスーパーラフィングジブ

オフセット 作業半径 (m)	5°		15°		30°		45°		60°	
	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)
16.0	78.6	12.0								
18.0	77.2	12.0	79.7	12.0						
20.0	75.8	12.0	78.3	12.0						
22.0	74.4	12.0	76.8	12.0	80.2	12.0				
24.0	73.0	12.0	75.4	12.0	78.6	12.0				
26.0	71.6	12.0	73.9	12.0	77.1	11.9	79.3	10.4		
28.0	70.1	12.0	72.5	12.0	75.3	11.0	77.6	10.0	78.9	9.1
30.0	68.6	12.0	70.8	11.5	73.6	10.2	75.7	9.4	77.0	8.9
32.0	66.9	11.3	69.0	10.6	71.8	9.5	73.8	8.8	75.0	8.4
34.0	65.1	10.3	67.2	9.8	69.9	8.9	71.9	8.3	72.9	7.9
36.0	63.2	9.1	65.4	9.0	68.1	8.3	69.9	7.7	70.8	7.5
38.0	61.2	7.7	63.6	8.3	66.2	7.7	67.9	7.3	68.7	7.1
40.0	59.1	6.4	61.6	7.3	64.2	7.2	65.8	6.8	66.4	6.7
42.0	57.0	5.2	59.4	6.0	62.2	6.7	63.7	6.4	64.0	6.4
44.0	54.9	4.1	57.2	4.9	60.0	5.8	61.4	6.1		
46.0	52.7	3.2	54.9	3.9	57.6	4.7	59.0	5.2		
48.0	50.3	2.3	52.6	2.9	55.1	3.7	56.3	4.1		
50.0	48.0	1.5	50.2	2.0	52.6	2.7	53.5	3.1		
52.0					49.9	1.8	50.6	2.1		
掛数	1		1		1		1		1	
危険角度(°)	46		46		47		47		60	
フック種類	12t		12t		12t		12t		12t	
フック質量(t)	0.42		0.42		0.42		0.42		0.42	

SB性能

40.9mブーム+2m+23mスーパーラフィングジブ

オフセット	5°		15°		30°		45°		60°	
作業半径 (m)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)
14.0	79.1	12.0								
16.0	77.5	12.0								
18.0	75.9	12.0	79.2	12.0						
20.0	74.3	12.0	77.6	12.0						
22.0	72.7	12.0	76.0	12.0	80.2	10.4				
24.0	71.0	12.0	74.2	11.5	78.4	10.1				
26.0	69.3	11.9	72.4	10.9	76.5	9.8	79.9	8.1		
28.0	67.5	11.1	70.5	10.3	74.6	9.4	77.8	7.8		
30.0	65.6	10.4	68.6	9.8	72.6	9.0	75.7	7.6	77.9	6.8
32.0	63.7	9.8	66.7	9.3	70.6	8.7	73.6	7.5	75.5	6.7
34.0	61.7	9.2	64.7	8.8	68.6	8.4	71.4	7.3	73.1	6.7
36.0	59.7	8.7	62.7	8.4	66.5	8.1	69.2	7.1	70.5	6.6
38.0	57.6	8.2	60.6	8.1	64.3	7.8	66.8	7.0	67.9	6.6
40.0	55.5	7.8	58.5	7.7	62.0	7.5	64.3	6.9	65.1	6.5
42.0	53.1	6.6	56.2	7.4	59.7	7.3	61.8	6.8	62.2	6.5
44.0	50.6	5.5	53.7	6.3	57.3	7.1	59.1	6.7		
46.0	48.1	4.6	51.1	5.3	54.5	6.2	56.2	6.5		
48.0	45.4	3.7	48.4	4.3	51.6	5.1	52.9	5.6		
50.0	42.6	2.8	45.5	3.4	48.4	4.1	49.3	4.4		
52.0	39.6	2.1	42.4	2.6	45.1	3.2				
54.0	36.4	1.4	39.0	1.8	41.4	2.3				
56.0					37.2	1.4				
掛数	1		1		1		1		1	
危険角度(°)	34		34		34		45		60	
フック種類	12t		12t		12t		12t		12t	
フック質量(t)	0.42		0.42		0.42		0.42		0.42	

SB性能

45.5mブーム+2m+23mスーパーラフィングジブ

オフセット	5°		15°		30°		45°		60°	
作業半径 (m)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)
16.0	78.7	12.0								
18.0	77.2	12.0								
20.0	75.8	12.0	78.9	12.0						
22.0	74.3	12.0	77.4	12.0						
24.0	72.9	12.0	75.9	12.0	79.7	10.2				
26.0	71.4	12.0	74.2	11.3	78.0	9.9				
28.0	69.8	11.8	72.5	10.7	76.3	9.6	79.2	7.9		
30.0	68.1	11.1	70.9	10.2	74.6	9.3	77.4	7.7	79.3	6.9
32.0	66.4	10.4	69.2	9.7	72.7	8.9	75.5	7.6	77.2	6.8
34.0	64.6	9.8	67.4	9.3	70.9	8.4	73.5	7.4	75.1	6.7
36.0	62.9	9.3	65.6	8.9	69.0	7.9	71.6	7.2	72.9	6.6
38.0	61.0	8.8	63.8	8.4	67.0	7.5	69.5	6.9	70.6	6.6
40.0	58.9	7.5	61.7	7.8	65.0	7.1	67.3	6.6	68.3	6.3
42.0	56.8	6.3	59.8	7.3	63.0	6.7	65.0	6.3	65.7	6.1
44.0	54.6	5.3	57.5	6.1	60.7	6.3	62.7	6.0	63.1	5.9
46.0	52.3	4.3	55.2	5.1	58.5	6.0	60.2	5.7		
48.0	49.9	3.4	52.8	4.1	56.0	5.0	57.7	5.5		
50.0	47.6	2.6	50.3	3.2	53.4	4.0	54.8	4.5		
52.0	45.0	1.8	47.7	2.4	50.6	3.1	51.6	3.5		
54.0			45.0	1.6	47.6	2.3	48.3	2.5		
56.0					44.4	1.5				
掛数	1		1		1		1		1	
危険角度(°)	41		42		42		45		60	
フック種類	12t		12t		12t		12t		12t	
フック質量(t)	0.42		0.42		0.42		0.42		0.42	

SB性能

50.0mブーム+2m+23mスーパーラフィングジブ

オフセット	5°		15°		30°		45°		60°	
作業半径 (m)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)
16.0	79.6	11.0								
18.0	78.3	11.0								
20.0	77.0	11.0	79.8	11.0						
22.0	75.7	11.0	78.5	11.0						
24.0	74.4	11.0	77.2	11.0						
26.0	73.0	11.0	75.8	11.0	79.3	10.1				
28.0	71.7	11.0	74.4	11.0	77.8	9.8				
30.0	70.3	11.0	72.9	10.6	76.3	9.4	78.8	7.8		
32.0	68.8	10.9	71.3	9.8	74.6	8.7	77.1	7.7	78.7	6.8
34.0	67.2	10.0	69.7	9.1	72.9	8.1	75.4	7.5	76.9	6.7
36.0	65.5	9.1	67.9	8.4	71.1	7.6	73.5	7.0	74.9	6.7
38.0	63.7	8.3	66.2	7.8	69.4	7.1	71.6	6.6	72.8	6.4
40.0	61.9	7.3	64.4	7.2	67.5	6.6	69.7	6.2	70.7	6.0
42.0	59.9	6.1	62.7	6.7	65.6	6.2	67.7	5.8	68.5	5.7
44.0	57.9	5.0	60.7	5.9	63.7	5.8	65.7	5.5	66.3	5.4
46.0	55.9	4.0	58.6	4.9	61.7	5.4	63.5	5.2	63.9	5.1
48.0	53.7	3.1	56.5	3.9	59.6	4.9	61.3	4.9		
50.0	51.6	2.3	54.3	3.1	57.3	4.0	59.0	4.5		
52.0	49.4	1.6	52.0	2.2	54.9	3.1	56.3	3.5		
54.0			49.6	1.5	52.4	2.2	53.5	2.6		
56.0							50.6	1.7		
掛数	1		1		1		1		1	
危険角度(°)	47		47		48		48		60	
フック種類	12t		12t		12t		12t		12t	
フック質量(t)	0.42		0.42		0.42		0.42		0.42	

SB性能

40.9mブーム+2m+27mスーパーラフィングジブ

オフセット 作業半径 (m)	5°		15°		30°		45°		60°	
	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)
14.0	80.3	12.0								
16.0	78.9	12.0								
18.0	77.4	12.0								
20.0	75.9	12.0	79.5	11.2						
22.0	74.4	12.0	77.9	10.7						
24.0	72.8	11.4	76.2	10.2						
26.0	71.1	10.6	74.5	9.6	79.2	7.9				
28.0	69.4	9.9	72.8	9.1	77.4	7.6				
30.0	67.7	9.2	71.1	8.6	75.7	7.4	79.4	6.3		
32.0	65.9	8.6	69.3	8.1	73.8	7.2	77.4	6.1	80.0	5.4
34.0	64.1	8.1	67.5	7.7	71.9	7.0	75.4	6.0	77.7	5.3
36.0	62.2	7.6	65.6	7.4	70.0	6.8	73.3	5.8	75.4	5.2
38.0	60.3	7.2	63.7	7.0	68.0	6.6	71.1	5.7	73.0	5.2
40.0	58.4	6.8	61.8	6.7	65.9	6.4	68.9	5.5	70.4	5.1
42.0	56.4	6.4	59.7	6.4	63.8	6.2	66.6	5.4	67.9	5.1
44.0	54.4	6.1	57.6	6.1	61.6	6.0	64.2	5.3	65.1	5.1
46.0	52.0	5.4	55.4	5.9	59.4	5.8	61.7	5.3	62.1	5.1
48.0	49.6	4.5	53.1	5.3	56.9	5.7	59.0	5.2		
50.0	47.2	3.7	50.6	4.4	54.3	5.4	56.1	5.1		
52.0	44.5	2.9	47.8	3.6	51.5	4.4	53.0	4.9		
54.0	41.8	2.2	45.0	2.8	48.3	3.5	49.3	3.9		
56.0	38.9	1.5	42.0	2.1	45.0	2.7				
58.0			38.8	1.4	41.4	1.9				
掛数	1		1		1		1		1	
危険角度(°)	35		36		36		45		60	
フック種類	12t		12t		12t		12t		12t	
フック質量(t)	0.42		0.42		0.42		0.42		0.42	

SB性能

45.5mブーム+2m+27mスーパーラフィングジブ

オフセット 作業半径 (m)	5°		15°		30°		45°		60°	
	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)
16.0	79.8	11.0								
18.0	78.4	11.0								
20.0	77.1	11.0	80.5	11.0						
22.0	75.7	11.0	79.2	10.9						
24.0	74.3	11.0	77.6	10.4						
26.0	73.0	11.0	76.2	10.0	80.3	8.0				
28.0	71.5	10.5	74.6	9.4	78.8	7.8				
30.0	69.9	9.8	73.0	8.9	77.1	7.5				
32.0	68.3	9.2	71.4	8.5	75.5	7.3	78.8	6.2		
34.0	66.6	8.6	69.8	8.1	73.8	7.1	76.9	6.0	79.2	5.3
36.0	65.0	8.1	68.1	7.7	72.1	7.0	75.2	5.9	77.1	5.3
38.0	63.3	7.7	66.4	7.4	70.3	6.8	73.3	5.8	75.0	5.2
40.0	61.5	7.3	64.6	7.0	68.5	6.4	71.3	5.6	72.8	5.1
42.0	59.7	6.9	62.8	6.7	66.5	6.1	69.3	5.5	70.6	5.1
44.0	57.8	6.1	60.9	6.4	64.6	5.8	67.2	5.4	68.1	5.1
46.0	55.7	5.1	59.0	6.0	62.6	5.5	64.9	5.1	65.7	5.0
48.0	53.6	4.2	56.8	5.1	60.4	5.2	62.7	4.9	63.0	4.8
50.0	51.3	3.4	54.5	4.2	58.3	4.9	60.2	4.7		
52.0	49.1	2.6	52.2	3.4	55.8	4.3	57.6	4.5		
54.0	46.7	1.9	49.8	2.6	53.3	3.4	54.9	3.9		
56.0			47.3	1.9	50.5	2.6	51.7	3.0		
58.0					47.6	1.8	48.3	2.1		
掛数	1		1		1		1		1	
危険角度(°)	43		43		43		45		60	
フック種類	12t		12t		12t		12t		12t	
フック質量(t)	0.42		0.42		0.42		0.42		0.42	

SB性能

50.0mブーム+2m+27mスーパーラフィングジブ

オフセット 作業半径 (m)	5°		15°		30°		45°		60°	
	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)
18.0	79.1	9.0								
20.0	77.9	9.0								
22.0	76.7	9.0	79.9	9.0						
24.0	75.4	9.0	78.6	9.0						
26.0	74.1	9.0	77.3	9.0						
28.0	72.9	9.0	76.0	9.0	80.0	7.9				
30.0	71.6	9.0	74.7	9.0	78.5	7.6				
32.0	70.3	9.0	73.3	8.8	77.0	7.4	80.1	6.3		
34.0	68.9	9.0	71.8	8.4	75.5	7.3	78.4	6.1		
36.0	67.4	8.6	70.3	7.9	73.9	7.0	76.8	6.0	78.6	5.3
38.0	65.9	8.0	68.6	7.3	72.3	6.6	75.0	5.8	76.7	5.2
40.0	64.3	7.4	67.0	6.8	70.6	6.2	73.3	5.7	74.8	5.2
42.0	62.5	6.8	65.3	6.3	68.9	5.8	71.5	5.4	72.8	5.1
44.0	60.7	5.8	63.6	5.9	67.1	5.4	69.5	5.1	70.7	4.9
46.0	58.8	4.8	61.9	5.5	65.3	5.1	67.6	4.8	68.5	4.7
48.0	56.8	3.9	59.9	4.9	63.4	4.7	65.6	4.5	66.2	4.4
50.0	54.8	3.1	57.9	4.0	61.4	4.4	63.4	4.2	63.8	4.2
52.0	52.8	2.3	55.8	3.1	59.5	4.2	61.3	4.0		
54.0	50.7	1.6	53.7	2.4	57.1	3.3	59.0	3.8		
56.0			51.4	1.7	54.8	2.5	56.3	3.0		
58.0					52.2	1.8	53.6	2.2		
掛数	1		1		1		1		1	
危険角度(°)	48		49		49		49		60	
フック種類	12t		12t		12t		12t		12t	
フック質量(t)	0.42		0.42		0.42		0.42		0.42	

SB性能

40.9mブーム+2m+31mスーパーラフィングジブ

オフセット 作業半径 (m)	5°		15°		30°		45°		60°	
	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)
16.0	79.7	9.0								
18.0	78.3	9.0								
20.0	76.9	9.0								
22.0	75.5	9.0	79.6	9.0						
24.0	74.1	9.0	78.1	8.7						
26.0	72.7	9.0	76.5	8.3						
28.0	71.2	8.9	74.9	8.0	80.0	6.4				
30.0	69.6	8.3	73.3	7.6	78.4	6.2				
32.0	67.9	7.8	71.7	7.3	76.7	6.1				
34.0	66.2	7.3	70.0	6.9	74.9	5.9	79.0	4.9		
36.0	64.5	6.8	68.3	6.6	73.2	5.7	77.0	4.8		
38.0	62.8	6.4	66.4	6.2	71.2	5.5	75.1	4.7	77.7	4.2
40.0	61.0	6.1	64.6	5.9	69.4	5.3	73.1	4.6	75.4	4.2
42.0	59.1	5.7	62.8	5.7	67.5	5.1	70.9	4.5	73.0	4.1
44.0	57.2	5.4	60.9	5.4	65.5	5.0	68.8	4.4	70.5	4.1
46.0	55.3	5.1	59.0	5.2	63.4	4.8	66.5	4.3	67.8	4.0
48.0	53.4	4.9	56.9	5.0	61.2	4.7	64.0	4.2	64.9	4.0
50.0	51.2	4.4	54.8	4.8	59.0	4.6	61.6	4.2	62.0	4.0
52.0	48.8	3.7	52.6	4.5	56.6	4.5	58.9	4.1		
54.0	46.4	2.9	50.1	3.7	54.2	4.4	56.1	4.1		
56.0	43.8	2.3	47.4	3.0	51.4	3.8	52.9	4.0		
58.0	41.2	1.7	44.7	2.3	48.3	3.0	49.4	3.4		
60.0			41.7	1.6	45.0	2.3				
62.0					41.4	1.6				
掛数	1		1		1		1		1	
危険角度(°)	37		37		37		45		60	
フック種類	12t		12t		12t		12t		12t	
フック質量(t)	0.42		0.42		0.42		0.42		0.42	

SB性能

45.5mブーム+2m+31mスーパーラフィングジブ

オフセット 作業半径 (m)	5°		15°		30°		45°		60°	
	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)
18.0	79.3	9.0								
20.0	78.0	9.0								
22.0	76.8	9.0	80.6	9.0						
24.0	75.5	9.0	79.3	9.0						
26.0	74.2	9.0	77.8	8.5						
28.0	72.9	9.0	76.4	8.2						
30.0	71.5	8.8	74.9	7.8	79.6	6.3				
32.0	70.0	8.3	73.5	7.5	78.0	6.1				
34.0	68.5	7.7	72.0	7.2	76.4	6.0	80.2	5.0		
36.0	66.9	7.3	70.4	6.8	74.9	5.8	78.5	4.9		
38.0	65.3	6.9	68.8	6.5	73.2	5.6	76.6	4.7	79.1	4.2
40.0	63.7	6.5	67.1	6.2	71.5	5.4	74.8	4.6	77.1	4.2
42.0	62.1	6.1	65.5	6.0	69.8	5.3	72.9	4.5	75.0	4.1
44.0	60.4	5.8	63.8	5.7	68.0	5.1	71.1	4.5	72.7	4.1
46.0	58.7	5.5	62.0	5.5	66.2	5.0	69.1	4.4	70.5	4.0
48.0	56.8	4.9	60.2	5.2	64.3	4.8	67.0	4.3	68.1	4.0
50.0	54.8	4.1	58.4	5.0	62.2	4.5	64.9	4.2	65.6	4.0
52.0	52.6	3.3	56.3	4.2	60.2	4.3	62.6	4.1	62.9	4.0
54.0	50.5	2.6	54.0	3.4	58.0	4.1	60.2	3.9		
56.0	48.2	2.0	51.7	2.7	55.8	3.7	57.6	3.7		
58.0			49.3	2.0	53.1	2.9	54.8	3.4		
60.0			46.8	1.4	50.4	2.2	51.7	2.6		
62.0					47.5	1.5	48.3	1.8		
掛数	1		1		1		1		1	
危険角度(°)	44		44		45		45		60	
フック種類	12t		12t		12t		12t		12t	
フック質量(t)	0.42		0.42		0.42		0.42		0.42	

SB性能

50.0mブーム+2m+31mスーパーラフィングジブ

オフセット 作業半径 (m)	5°		15°		30°		45°		60°	
	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)
18.0	80.0	8.0								
20.0	78.8	8.0								
22.0	77.7	8.0								
24.0	76.6	8.0	80.1	8.0						
26.0	75.4	8.0	78.9	8.0						
28.0	74.1	8.0	77.7	8.0						
30.0	72.9	8.0	76.5	8.0	80.6	6.4				
32.0	71.7	8.0	75.0	7.7	79.3	6.2				
34.0	70.5	8.0	73.7	7.4	77.8	6.1				
36.0	69.2	7.7	72.3	7.1	76.4	5.9	79.7	4.9		
38.0	67.7	7.3	70.9	6.8	74.8	5.7	78.1	4.8		
40.0	66.2	6.9	69.4	6.4	73.4	5.5	76.5	4.7	78.6	4.2
42.0	64.7	6.5	67.8	6.0	71.8	5.4	74.8	4.6	76.7	4.1
44.0	63.2	6.0	66.3	5.6	70.2	5.1	73.1	4.5	74.8	4.1
46.0	61.5	5.5	64.6	5.2	68.4	4.7	71.3	4.4	72.8	4.1
48.0	59.7	4.6	62.9	4.8	66.7	4.4	69.4	4.2	70.7	4.0
50.0	57.8	3.8	61.3	4.5	64.9	4.2	67.5	4.0	68.5	3.9
52.0	55.9	3.0	59.3	4.0	63.1	3.9	65.5	3.7	66.1	3.7
54.0	53.9	2.3	57.4	3.2	61.2	3.7	63.4	3.5		
56.0	51.9	1.7	55.2	2.5	59.3	3.4	61.2	3.3		
58.0			53.2	1.8	56.9	2.8	58.9	3.1		
60.0					54.7	2.1	56.4	2.6		
62.0					52.1	1.4	53.6	1.8		
掛数	1		1		1		1		1	
危険角度(°)	49		50		50		50		60	
フック種類	12t		12t		12t		12t		12t	
フック質量(t)	0.42		0.42		0.42		0.42		0.42	

SC性能

40.9mブーム+2m+10mスーパーラフィングジブ

オフセット 作業半径 (m)	5°		15°		30°		45°		60°	
	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)
10.0	79.0	24.0								
11.0	78.1	24.0	79.8	24.0						
12.0	77.1	24.0	78.8	24.0						
14.0	75.1	24.0	76.8	24.0	79.1	24.0				
16.0	73.0	24.0	74.7	24.0	77.0	24.0	78.5	21.4	79.6	19.9
18.0	71.0	24.0	72.7	24.0	74.8	23.3	76.2	20.6	77.1	19.4
20.0	68.8	22.4	70.5	23.4	72.6	22.3	73.9	20.0	74.6	19.1
22.0	66.3	18.4	68.0	19.3	70.1	20.4	71.4	19.0	72.1	18.3
24.0	63.7	15.2	65.4	16.0	67.4	16.9	68.9	17.6	69.4	17.4
26.0	61.2	12.6	62.8	13.3	64.8	14.1	66.0	14.6	66.4	14.8
28.0	58.5	10.4	60.1	11.0	62.0	11.7	63.2	12.1	63.4	12.3
30.0	55.8	8.6	57.4	9.1	59.2	9.7	60.2	10.0		
32.0	53.0	6.6	54.6	7.3	56.2	7.9	57.1	8.2		
34.0	50.1	4.8	51.6	5.4	53.2	6.0	53.8	6.3		
36.0	46.9	3.3	48.4	3.8	49.9	4.3	50.3	4.5		
38.0					46.4	2.7				
掛数	2		2		2		2		2	
危険角度(°)	43		44		44		45		60	
フック種類	24t		24t		24t		24t		24t	
フック質量(t)	0.88		0.88		0.88		0.88		0.88	

SC性能

45.5mブーム+2m+10mスーパーラフィングジブ

オフセット 作業半径 (m)	5°		15°		30°		45°		60°	
	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)
11.0	79.4	24.0								
12.0	78.5	24.0								
14.0	76.8	24.0	78.3	24.0						
16.0	75.0	24.0	76.6	24.0	78.6	24.0				
18.0	73.2	24.0	74.8	24.0	76.6	22.1	78.0	19.8	78.8	18.6
20.0	71.3	22.4	72.9	23.4	74.5	20.4	75.8	18.5	76.5	17.5
22.0	69.0	18.4	70.6	19.2	72.4	18.9	73.7	17.3	74.3	16.5
24.0	66.7	15.2	68.3	15.9	70.2	16.9	71.4	16.2	71.9	15.6
26.0	64.4	12.5	65.9	13.2	67.8	14.1	69.1	14.7	69.6	14.8
28.0	62.0	10.4	63.6	11.0	65.3	11.7	66.5	12.2	66.9	12.4
30.0	59.6	8.5	61.1	9.0	62.8	9.7	63.8	10.1	64.1	10.2
32.0	57.1	6.5	58.6	7.2	60.3	8.0	61.2	8.3		
34.0	54.6	4.7	56.0	5.4	57.6	6.1	58.4	6.5		
36.0	51.8	3.2	53.2	3.7	54.8	4.3	55.4	4.6		
38.0					51.8	2.8	52.3	3.0		
掛数	2		2		2		2		2	
危険角度(°)	49		49		49		49		60	
フック種類	24t		24t		24t		24t		24t	
フック質量(t)	0.88		0.88		0.88		0.88		0.88	

SC性能

50.0mブーム+2m+10mスーパーラフィングジブ

オフセット 作業半径 (m)	5°		15°		30°		45°		60°	
	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)
12.0	79.5	20.0								
14.0	77.9	20.0	79.4	20.0						
16.0	76.4	20.0	77.8	20.0	79.7	20.0				
18.0	74.7	20.0	76.2	20.0	78.0	20.0	79.4	19.6		
20.0	73.2	20.0	74.6	20.0	76.3	19.6	77.5	18.0	78.2	17.1
22.0	71.3	18.3	72.8	19.2	74.5	17.9	75.6	16.6	76.2	15.9
24.0	69.2	15.1	70.7	15.9	72.5	16.4	73.5	15.3	74.0	14.8
26.0	67.1	12.5	68.5	13.2	70.4	14.1	71.5	14.2	72.0	13.8
28.0	65.0	10.3	66.4	10.9	68.1	11.7	69.3	12.2	69.7	12.5
30.0	62.8	8.5	64.2	9.0	65.8	9.7	66.9	10.2	67.2	10.3
32.0	60.5	6.4	61.9	7.2	63.5	8.0	64.5	8.4	64.7	8.5
34.0	58.2	4.7	59.6	5.3	61.1	6.1	62.1	6.5		
36.0	55.8	3.1	57.1	3.7	58.6	4.4	59.4	4.7		
38.0					56.1	2.8	56.7	3.1		
掛数	2		2		2		2		2	
危険角度(°)	53		54		54		54		60	
フック種類	24t		24t		24t		24t		24t	
フック質量(t)	0.88		0.88		0.88		0.88		0.88	

SC性能

40.9mブーム+2m+15mスーパーラフィングジブ

オフセット 作業半径 (m)	5°		15°		30°		45°		60°	
	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)
11.0	79.3	12.0								
12.0	78.3	12.0								
14.0	76.5	12.0	78.9	12.0						
16.0	74.6	12.0	77.0	12.0						
18.0	72.7	12.0	75.1	12.0	78.3	12.0				
20.0	70.8	12.0	73.2	12.0	76.3	12.0	78.8	12.0		
22.0	68.8	12.0	71.2	12.0	74.3	12.0	76.7	12.0	78.2	12.0
24.0	66.8	12.0	69.2	12.0	72.2	12.0	74.4	12.0	75.9	12.0
26.0	64.8	12.0	67.1	12.0	70.0	12.0	72.2	12.0	73.4	12.0
28.0	62.7	12.0	64.9	12.0	67.8	12.0	69.9	12.0	70.9	12.0
30.0	60.4	10.1	62.7	10.9	65.5	11.9	67.4	12.0	68.2	11.9
32.0	57.9	8.5	60.1	9.2	62.9	10.1	64.7	10.7	65.3	10.9
34.0	55.4	6.9	57.6	7.7	60.3	8.5	61.9	9.0	62.2	9.2
36.0	52.7	5.3	54.9	6.1	57.5	7.1	59.0	7.5		
38.0	50.0	3.9	52.1	4.6	54.6	5.5	55.8	6.0		
40.0	47.1	2.7	49.2	3.3	51.5	4.0	52.5	4.4		
42.0	44.1	1.5	46.2	2.1	48.2	2.7	48.9	3.0		
掛数	1		1		1		1		1	
危険角度(°)	42		42		43		45		60	
フック種類	12t		12t		12t		12t		12t	
フック質量(t)	0.42		0.42		0.42		0.42		0.42	

SC性能

45.5mブーム+2m+15mスーパーラフィングジブ

オフセット 作業半径 (m)	5°		15°		30°		45°		60°	
	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)
14.0	77.8	12.0								
16.0	76.1	12.0	78.4	12.0						
18.0	74.4	12.0	76.6	12.0						
20.0	72.8	12.0	74.9	12.0	77.8	12.0				
22.0	71.0	12.0	73.2	12.0	76.0	12.0	78.2	12.0		
24.0	69.3	12.0	71.4	12.0	74.2	12.0	76.2	12.0	77.6	12.0
26.0	67.5	12.0	69.5	12.0	72.2	12.0	74.2	12.0	75.4	11.7
28.0	65.6	11.9	67.7	12.0	70.3	12.0	72.2	11.7	73.1	11.2
30.0	63.5	10.0	65.6	10.8	68.3	11.8	70.0	11.1	70.9	10.7
32.0	61.2	8.4	63.4	9.1	66.1	10.0	67.7	10.5	68.4	10.2
34.0	59.0	6.7	61.1	7.6	63.7	8.5	65.3	9.0	65.8	9.3
36.0	56.6	5.1	58.7	6.0	61.2	7.1	62.7	7.6	63.0	7.7
38.0	54.2	3.7	56.2	4.5	58.6	5.5	60.0	6.1		
40.0	51.7	2.5	53.7	3.2	56.0	4.0	57.2	4.5		
42.0			51.1	2.0	53.2	2.7	54.2	3.1		
44.0					50.3	1.5	51.1	1.8		
掛数	1		1		1		1		1	
危険角度(°)	48		48		48		48		60	
フック種類	12t		12t		12t		12t		12t	
フック質量(t)	0.42		0.42		0.42		0.42		0.42	

SC性能

50.0mブーム+2m+15mスーパーラフィングジブ

オフセット 作業半径 (m)	5°		15°		30°		45°		60°	
	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)
14.0	78.9	12.0								
16.0	77.4	12.0	79.4	12.0						
18.0	76.0	12.0	78.0	12.0						
20.0	74.5	12.0	76.4	12.0	79.1	12.0				
22.0	72.9	12.0	74.9	12.0	77.5	12.0	79.6	12.0		
24.0	71.3	12.0	73.3	12.0	75.9	12.0	77.8	12.0	79.1	12.0
26.0	69.7	12.0	71.7	12.0	74.2	12.0	76.1	12.0	77.1	11.5
28.0	68.1	11.8	70.0	12.0	72.6	12.0	74.3	11.4	75.2	10.9
30.0	66.1	9.9	68.2	10.7	70.7	11.4	72.3	10.6	73.1	10.2
32.0	64.1	8.3	66.1	9.0	68.6	10.0	70.3	9.9	70.9	9.6
34.0	62.0	6.6	64.1	7.5	66.5	8.4	68.2	9.0	68.7	9.1
36.0	59.9	5.0	61.9	5.9	64.3	7.0	65.8	7.6	66.3	7.8
38.0	57.7	3.6	59.7	4.4	62.0	5.4	63.4	6.1	63.7	6.3
40.0	55.4	2.3	57.4	3.1	59.7	4.0	60.9	4.6		
42.0			55.1	1.9	57.2	2.7	58.4	3.2		
44.0							55.7	1.9		
掛数	1		1		1		1		1	
危険角度(°)	52		53		53		53		60	
フック種類	12t		12t		12t		12t		12t	
フック質量(t)	0.42		0.42		0.42		0.42		0.42	

SC性能

40.9mブーム+2m+19mスーパーラフィングジブ

オフセット	5°		15°		30°		45°		60°	
作業半径 (m)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)
12.0	79.5	12.0								
14.0	77.8	12.0								
16.0	76.1	12.0	79.0	12.0						
18.0	74.4	12.0	77.3	12.0						
20.0	72.7	12.0	75.5	12.0	79.4	12.0				
22.0	70.9	12.0	73.7	12.0	77.4	12.0				
24.0	69.1	12.0	71.8	12.0	75.5	12.0	78.4	10.4		
26.0	67.2	12.0	69.9	12.0	73.6	11.6	76.2	10.2	78.0	9.1
28.0	65.3	12.0	68.0	12.0	71.5	11.1	74.0	9.9	75.7	9.0
30.0	63.2	11.0	66.0	11.4	69.4	10.7	71.8	9.7	73.2	8.9
32.0	61.0	9.4	63.7	10.2	67.2	10.3	69.5	9.4	70.7	8.8
34.0	58.7	7.9	61.5	8.7	64.9	9.8	67.1	9.2	68.0	8.8
36.0	56.3	6.6	59.0	7.4	62.4	8.3	64.6	9.0	65.3	8.8
38.0	53.9	5.1	56.5	6.1	59.8	7.1	61.8	7.7	62.2	7.9
40.0	51.3	3.9	53.9	4.7	57.1	5.8	58.9	6.4		
42.0	48.6	2.7	51.2	3.5	54.2	4.4	55.7	5.0		
44.0	45.8	1.7	48.4	2.4	51.2	3.2	52.5	3.6		
46.0					48.1	2.1	48.9	2.4		
掛数	1		1		1		1		1	
危険角度(°)	43		44		44		45		60	
フック種類	12t		12t		12t		12t		12t	
フック質量(t)	0.42		0.42		0.42		0.42		0.42	

SC性能

45.5mブーム+2m+19mスーパーラフィングジブ

オフセット	5°		15°		30°		45°		60°	
作業半径 (m)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)
14.0	79.0	12.0								
16.0	77.4	12.0								
18.0	75.9	12.0	78.5	12.0						
20.0	74.3	12.0	77.0	12.0						
22.0	72.8	12.0	75.3	12.0	78.9	12.0				
24.0	71.1	12.0	73.7	12.0	77.1	12.0	79.7	10.6		
26.0	69.5	12.0	72.1	12.0	75.4	11.9	77.9	10.3	79.5	9.2
28.0	67.8	12.0	70.3	12.0	73.5	11.2	76.0	10.1	77.4	9.1
30.0	65.9	10.8	68.6	11.8	71.6	10.5	74.0	9.6	75.3	9.0
32.0	63.9	9.2	66.6	10.1	69.6	9.9	71.9	9.1	73.0	8.6
34.0	61.8	7.8	64.4	8.6	67.6	9.3	69.7	8.6	70.7	8.3
36.0	59.7	6.3	62.2	7.3	65.4	8.3	67.5	8.2	68.3	7.9
38.0	57.5	4.9	60.0	5.9	63.2	7.0	65.2	7.7	65.8	7.6
40.0	55.2	3.6	57.7	4.5	60.8	5.7	62.6	6.4	63.1	6.6
42.0	52.8	2.5	55.3	3.3	58.2	4.3	60.0	5.0		
44.0			52.8	2.2	55.6	3.1	57.2	3.7		
46.0					52.9	2.0	54.2	2.5		
掛数	1		1		1		1		1	
危険角度(°)	49		49		50		50		60	
フック種類	12t		12t		12t		12t		12t	
フック質量(t)	0.42		0.42		0.42		0.42		0.42	

SC性能

50.0mブーム+2m+19mスーパーラフィングジブ

オフセット	5°		15°		30°		45°		60°	
作業半径 (m)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)
16.0	78.6	12.0								
18.0	77.2	12.0	79.7	12.0						
20.0	75.8	12.0	78.3	12.0						
22.0	74.4	12.0	76.8	12.0	80.2	12.0				
24.0	73.0	12.0	75.4	12.0	78.6	12.0				
26.0	71.6	12.0	73.9	12.0	77.1	11.9	79.3	10.4		
28.0	70.1	12.0	72.5	12.0	75.3	11.0	77.6	10.0	78.9	9.1
30.0	68.3	10.7	70.8	11.5	73.6	10.2	75.7	9.4	77.0	8.9
32.0	66.4	9.0	68.9	10.0	71.8	9.5	73.8	8.8	75.0	8.4
34.0	64.5	7.6	67.0	8.5	69.9	8.9	71.9	8.3	72.9	7.9
36.0	62.5	6.1	65.0	7.2	68.1	8.2	69.9	7.7	70.8	7.5
38.0	60.5	4.7	63.0	5.7	66.0	7.0	67.9	7.3	68.7	7.1
40.0	58.4	3.4	60.8	4.4	63.8	5.6	65.7	6.4	66.4	6.7
42.0	56.3	2.2	58.6	3.1	61.6	4.3	63.4	5.1	63.7	5.3
44.0			56.4	2.0	59.2	3.1	60.8	3.7		
46.0					56.8	2.0	58.3	2.5		
掛数	1		1		1		1		1	
危険角度(°)	53		54		54		54		60	
フック種類	12t		12t		12t		12t		12t	
フック質量(t)	0.42		0.42		0.42		0.42		0.42	

SC性能

40.9mブーム+2m+23mスーパーラフィングジブ

オフセット 作業半径 (m)	5°		15°		30°		45°		60°	
	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)
14.0	79.1	12.0								
16.0	77.5	12.0								
18.0	75.9	12.0	79.2	12.0						
20.0	74.3	12.0	77.6	12.0						
22.0	72.7	12.0	76.0	12.0	80.2	10.4				
24.0	71.0	12.0	74.2	11.5	78.4	10.1				
26.0	69.3	11.9	72.4	10.9	76.5	9.8	79.9	8.1		
28.0	67.5	11.1	70.5	10.3	74.6	9.4	77.8	7.8		
30.0	65.6	10.4	68.6	9.8	72.6	9.0	75.7	7.6	77.9	6.8
32.0	63.7	9.8	66.7	9.3	70.6	8.7	73.6	7.5	75.5	6.7
34.0	61.7	8.7	64.7	8.8	68.6	8.4	71.4	7.3	73.1	6.7
36.0	59.5	7.4	62.7	8.3	66.5	8.1	69.2	7.1	70.5	6.6
38.0	57.2	6.2	60.4	7.1	64.3	7.8	66.8	7.0	67.9	6.6
40.0	54.9	4.9	58.1	6.0	61.9	7.0	64.3	6.9	65.1	6.5
42.0	52.5	3.8	55.6	4.7	59.4	6.0	61.8	6.6	62.2	6.5
44.0	50.0	2.7	53.1	3.6	56.8	4.7	58.9	5.5		
46.0	47.4	1.8	50.4	2.6	53.9	3.6	55.8	4.2		
48.0			47.7	1.6	51.0	2.5	52.4	3.0		
50.0					47.8	1.5	48.9	1.9		
掛数	1		1		1		1		1	
危険角度(°)	44		45		45		45		60	
フック種類	12t		12t		12t		12t		12t	
フック質量(t)	0.42		0.42		0.42		0.42		0.42	

SC性能

45.5mブーム+2m+23mスーパーラフィングジブ

オフセット 作業半径 (m)	5°		15°		30°		45°		60°	
	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)
16.0	78.7	12.0								
18.0	77.2	12.0								
20.0	75.8	12.0	78.9	12.0						
22.0	74.3	12.0	77.4	12.0						
24.0	72.9	12.0	75.9	12.0	79.7	10.2				
26.0	71.4	12.0	74.2	11.3	78.0	9.9				
28.0	69.8	11.8	72.5	10.7	76.3	9.6	79.2	7.9		
30.0	68.1	11.1	70.9	10.2	74.6	9.3	77.4	7.7	79.3	6.9
32.0	66.3	9.9	69.2	9.7	72.7	8.9	75.5	7.6	77.2	6.8
34.0	64.4	8.5	67.4	9.3	70.9	8.4	73.5	7.4	75.1	6.7
36.0	62.4	7.2	65.4	8.1	69.0	7.9	71.6	7.2	72.9	6.6
38.0	60.3	5.9	63.4	7.0	67.0	7.5	69.5	6.9	70.6	6.6
40.0	58.2	4.6	61.2	5.7	64.9	6.9	67.3	6.6	68.3	6.3
42.0	56.1	3.5	59.1	4.5	62.7	5.8	65.0	6.3	65.7	6.1
44.0	53.9	2.4	56.7	3.4	60.3	4.6	62.6	5.5	63.1	5.8
46.0			54.4	2.4	57.8	3.5	59.9	4.2		
48.0			52.0	1.4	55.3	2.4	57.1	3.0		
50.0							54.2	2.0		
掛数	1		1		1		1		1	
危険角度(°)	50		50		51		51		60	
フック種類	12t		12t		12t		12t		12t	
フック質量(t)	0.42		0.42		0.42		0.42		0.42	

SC性能

50.0mブーム+2m+23mスーパーラフィングジブ

オフセット 作業半径 (m)	5°		15°		30°		45°		60°	
	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)
16.0	79.6	11.0								
18.0	78.3	11.0								
20.0	77.0	11.0	79.8	11.0						
22.0	75.7	11.0	78.5	11.0						
24.0	74.4	11.0	77.2	11.0						
26.0	73.0	11.0	75.8	11.0	79.3	10.1				
28.0	71.7	11.0	74.4	11.0	77.8	9.8				
30.0	70.3	11.0	72.9	10.6	76.3	9.4	78.8	7.8		
32.0	68.6	9.7	71.3	9.8	74.6	8.7	77.1	7.7	78.7	6.8
34.0	66.8	8.3	69.7	9.1	72.9	8.1	75.4	7.5	76.9	6.7
36.0	64.9	7.1	67.8	8.0	71.1	7.6	73.5	7.0	74.9	6.7
38.0	63.0	5.6	66.0	6.8	69.4	7.1	71.6	6.6	72.8	6.4
40.0	61.1	4.4	63.9	5.5	67.5	6.6	69.7	6.2	70.7	6.0
42.0	59.1	3.2	62.0	4.3	65.5	5.7	67.7	5.8	68.5	5.7
44.0	57.0	2.2	59.9	3.2	63.3	4.5	65.6	5.4	66.3	5.4
46.0			57.7	2.2	61.1	3.4	63.3	4.2	63.7	4.5
48.0					58.8	2.3	60.8	3.1		
50.0							58.3	2.0		
掛数	1		1		1		1		1	
危険角度(°)	54		55		55		55		60	
フック種類	12t		12t		12t		12t		12t	
フック質量(t)	0.42		0.42		0.42		0.42		0.42	

SC性能

40.9mブーム+2m+27mスーパーラフィングジブ

オフセット 作業半径 (m)	5°		15°		30°		45°		60°	
	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)
14.0	80.3	12.0								
16.0	78.9	12.0								
18.0	77.4	12.0								
20.0	75.9	12.0	79.5	11.2						
22.0	74.4	12.0	77.9	10.7						
24.0	72.8	11.4	76.2	10.2						
26.0	71.1	10.6	74.5	9.6	79.2	7.9				
28.0	69.4	9.9	72.8	9.1	77.4	7.6				
30.0	67.7	9.2	71.1	8.6	75.7	7.4	79.4	6.3		
32.0	65.9	8.6	69.3	8.1	73.8	7.2	77.4	6.1	80.0	5.4
34.0	64.1	8.1	67.5	7.7	71.9	7.0	75.4	6.0	77.7	5.3
36.0	62.2	7.6	65.6	7.4	70.0	6.8	73.3	5.8	75.4	5.2
38.0	60.3	7.0	63.7	7.0	68.0	6.6	71.1	5.7	73.0	5.2
40.0	58.2	5.9	61.8	6.7	65.9	6.4	68.9	5.5	70.4	5.1
42.0	55.9	4.7	59.6	5.8	63.8	6.2	66.6	5.4	67.9	5.1
44.0	53.7	3.7	57.2	4.7	61.6	6.0	64.2	5.3	65.1	5.1
46.0	51.3	2.7	54.8	3.7	59.1	4.9	61.7	5.3	62.1	5.1
48.0	48.8	1.8	52.3	2.7	56.4	3.9	58.9	4.6		
50.0			49.8	1.8	53.7	2.9	55.8	3.5		
52.0					50.8	1.9	52.5	2.5		
掛数	1		1		1		1		1	
危険角度(°)	46		46		47		47		60	
フック種類	12t		12t		12t		12t		12t	
フック質量(t)	0.42		0.42		0.42		0.42		0.42	

SC性能

45.5mブーム+2m+27mスーパーラフィングジブ

オフセット 作業半径 (m)	5°		15°		30°		45°		60°	
	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)
16.0	79.8	11.0								
18.0	78.4	11.0								
20.0	77.1	11.0	80.5	11.0						
22.0	75.7	11.0	79.2	10.9						
24.0	74.3	11.0	77.6	10.4						
26.0	73.0	11.0	76.2	10.0	80.3	8.0				
28.0	71.5	10.5	74.6	9.4	78.8	7.8				
30.0	69.9	9.8	73.0	8.9	77.1	7.5				
32.0	68.3	9.2	71.4	8.5	75.5	7.3	78.8	6.2		
34.0	66.6	8.6	69.8	8.1	73.8	7.1	76.9	6.0	79.2	5.3
36.0	64.9	7.9	68.1	7.7	72.1	7.0	75.2	5.9	77.1	5.3
38.0	63.0	6.8	66.4	7.4	70.3	6.8	73.3	5.8	75.0	5.2
40.0	61.0	5.5	64.5	6.7	68.5	6.4	71.3	5.6	72.8	5.1
42.0	59.0	4.4	62.5	5.6	66.5	6.1	69.3	5.5	70.6	5.1
44.0	56.9	3.3	60.3	4.4	64.6	5.8	67.2	5.4	68.1	5.1
46.0	54.8	2.4	58.2	3.4	62.4	4.8	64.9	5.1	65.7	5.0
48.0			56.0	2.5	60.0	3.7	62.6	4.6	63.0	4.8
50.0					57.6	2.7	59.9	3.5		
52.0					55.0	1.8	57.1	2.5		
54.0							54.2	1.5		
掛数	1		1		1		1		1	
危険角度(°)	51		52		52		52		60	
フック種類	12t		12t		12t		12t		12t	
フック質量(t)	0.42		0.42		0.42		0.42		0.42	

SC性能

50.0mブーム+2m+27mスーパーラフィングジブ

オフセット 作業半径 (m)	5°		15°		30°		45°		60°	
	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)
18.0	79.1	9.0								
20.0	77.9	9.0								
22.0	76.7	9.0	79.9	9.0						
24.0	75.4	9.0	78.6	9.0						
26.0	74.1	9.0	77.3	9.0						
28.0	72.9	9.0	76.0	9.0	80.0	7.9				
30.0	71.6	9.0	74.7	9.0	78.5	7.6				
32.0	70.3	9.0	73.3	8.8	77.0	7.4	80.1	6.3		
34.0	68.9	8.9	71.8	8.4	75.5	7.3	78.4	6.1		
36.0	67.1	7.7	70.3	7.9	73.9	7.0	76.8	6.0	78.6	5.3
38.0	65.4	6.5	68.6	7.3	72.3	6.6	75.0	5.8	76.7	5.2
40.0	63.6	5.2	66.9	6.5	70.6	6.2	73.3	5.7	74.8	5.2
42.0	61.6	4.1	65.0	5.3	68.9	5.8	71.5	5.4	72.8	5.1
44.0	59.8	3.0	63.0	4.2	67.1	5.4	69.5	5.1	70.7	4.9
46.0	57.9	2.1	61.0	3.2	65.1	4.6	67.6	4.8	68.5	4.7
48.0			59.0	2.2	63.0	3.6	65.6	4.5	66.2	4.4
50.0					60.7	2.6	63.2	3.5	63.7	3.9
52.0					58.6	1.7	60.8	2.5		
54.0							58.2	1.5		
掛数	1		1		1		1		1	
危険角度(°)	55		56		56		56		60	
フック種類	12t		12t		12t		12t		12t	
フック質量(t)	0.42		0.42		0.42		0.42		0.42	

SC性能

40.9mブーム+2m+31mスーパーラフィングジブ

オフセット	5°		15°		30°		45°		60°	
作業半径 (m)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)
16.0	79.7	9.0								
18.0	78.3	9.0								
20.0	76.9	9.0								
22.0	75.5	9.0	79.6	9.0						
24.0	74.1	9.0	78.1	8.7						
26.0	72.7	9.0	76.5	8.3						
28.0	71.2	8.9	74.9	8.0	80.0	6.4				
30.0	69.6	8.3	73.3	7.6	78.4	6.2				
32.0	67.9	7.8	71.7	7.3	76.7	6.1				
34.0	66.2	7.3	70.0	6.9	74.9	5.9	79.0	4.9		
36.0	64.5	6.8	68.3	6.6	73.2	5.7	77.0	4.8		
38.0	62.8	6.4	66.4	6.2	71.2	5.5	75.1	4.7	77.7	4.2
40.0	61.0	6.1	64.6	5.9	69.4	5.3	73.1	4.6	75.4	4.2
42.0	59.1	5.5	62.8	5.7	67.5	5.1	70.9	4.5	73.0	4.1
44.0	56.9	4.5	60.9	5.4	65.5	5.0	68.8	4.4	70.5	4.1
46.0	54.8	3.5	58.8	4.6	63.4	4.8	66.5	4.3	67.8	4.0
48.0	52.6	2.7	56.5	3.7	61.2	4.7	64.0	4.2	64.9	4.0
50.0	50.2	1.9	54.1	2.8	58.8	4.1	61.6	4.2	62.0	4.0
52.0			51.7	2.0	56.2	3.1	58.8	4.0		
54.0					53.5	2.3	55.8	3.0		
56.0					50.7	1.5	52.4	2.0		
掛数	1		1		1		1		1	
危険角度(°)	47		48		48		48		60	
フック種類	12t		12t		12t		12t		12t	
フック質量(t)	0.42		0.42		0.42		0.42		0.42	

SC性能

45.5mブーム+2m+31mスーパーラフィングジブ

オフセット	5°		15°		30°		45°		60°	
作業半径 (m)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)
18.0	79.3	9.0								
20.0	78.0	9.0								
22.0	76.8	9.0	80.6	9.0						
24.0	75.5	9.0	79.3	9.0						
26.0	74.2	9.0	77.8	8.5						
28.0	72.9	9.0	76.4	8.2						
30.0	71.5	8.8	74.9	7.8	79.6	6.3				
32.0	70.0	8.3	73.5	7.5	78.0	6.1				
34.0	68.5	7.7	72.0	7.2	76.4	6.0	80.2	5.0		
36.0	66.9	7.3	70.4	6.8	74.9	5.8	78.5	4.9		
38.0	65.3	6.9	68.8	6.5	73.2	5.6	76.6	4.7	79.1	4.2
40.0	63.7	6.3	67.1	6.2	71.5	5.4	74.8	4.6	77.1	4.2
42.0	61.8	5.2	65.5	6.0	69.8	5.3	72.9	4.5	75.0	4.1
44.0	59.8	4.1	63.7	5.4	68.0	5.1	71.1	4.5	72.7	4.1
46.0	57.8	3.2	61.6	4.4	66.2	5.0	69.1	4.4	70.5	4.0
48.0	55.8	2.3	59.5	3.4	64.3	4.8	67.0	4.3	68.1	4.0
50.0			57.4	2.5	62.0	3.9	64.9	4.2	65.6	4.0
52.0			55.3	1.7	59.7	3.0	62.6	3.9	62.9	4.0
54.0					57.3	2.1	59.9	2.9		
56.0							57.1	2.0		
掛数	1		1		1		1		1	
危険角度(°)	52		53		53		53		60	
フック種類	12t		12t		12t		12t		12t	
フック質量(t)	0.42		0.42		0.42		0.42		0.42	

SC性能

50.0mブーム+2m+31mスーパーラフィングジブ

オフセット	5°		15°		30°		45°		60°	
作業半径 (m)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)
18.0	80.0	8.0								
20.0	78.8	8.0								
22.0	77.7	8.0								
24.0	76.6	8.0	80.1	8.0						
26.0	75.4	8.0	78.9	8.0						
28.0	74.1	8.0	77.7	8.0						
30.0	72.9	8.0	76.5	8.0	80.6	6.4				
32.0	71.7	8.0	75.0	7.7	79.3	6.2				
34.0	70.5	8.0	73.7	7.4	77.8	6.1				
36.0	69.2	7.7	72.3	7.1	76.4	5.9	79.7	4.9		
38.0	67.6	7.1	70.9	6.8	74.8	5.7	78.1	4.8		
40.0	65.9	6.0	69.4	6.4	73.4	5.5	76.5	4.7	78.6	4.2
42.0	64.1	4.8	67.8	6.0	71.8	5.4	74.8	4.6	76.7	4.1
44.0	62.3	3.8	66.1	5.1	70.2	5.1	73.1	4.5	74.8	4.1
46.0	60.5	2.9	64.2	4.1	68.4	4.7	71.3	4.4	72.8	4.1
48.0	58.6	2.0	62.2	3.2	66.7	4.4	69.4	4.2	70.7	4.0
50.0			60.3	2.3	64.7	3.8	67.5	4.0	68.5	3.9
52.0					62.6	2.8	65.5	3.7	66.1	3.7
54.0					60.5	2.0	63.2	2.9		
56.0							60.7	2.0		
掛数	1		1		1		1		1	
危険角度(°)	56		57		57		57		60	
フック種類	12t		12t		12t		12t		12t	
フック質量(t)	0.42		0.42		0.42		0.42		0.42	

SD性能

40.9mブーム+2m+10mスーパーラフィングジブ

オフセット	5°		15°		30°		45°		60°	
作業半径 (m)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)
10.0	79.0	24.0								
11.0	78.1	24.0	79.8	24.0						
12.0	77.1	24.0	78.8	24.0						
14.0	75.1	24.0	76.8	24.0	79.1	24.0				
16.0	73.0	24.0	74.7	24.0	77.0	24.0	78.5	21.4	79.6	19.9
18.0	70.7	20.1	72.5	21.2	74.7	22.7	76.2	20.6	77.1	19.4
20.0	68.2	16.0	70.0	16.9	72.2	18.2	73.8	19.1	74.6	19.1
22.0	65.8	12.7	67.5	13.6	69.6	14.6	71.1	15.4	71.9	15.8
24.0	63.3	10.2	65.0	10.9	67.0	11.8	68.4	12.4	69.0	12.8
26.0	60.7	8.0	62.3	8.7	64.3	9.5	65.6	10.0	66.0	10.2
28.0	58.0	5.7	59.7	6.5	61.6	7.4	62.7	7.9	63.0	8.1
30.0	55.3	3.7	56.9	4.4	58.7	5.3	59.8	5.8		
32.0					55.7	3.4	56.6	3.8		
掛数	2		2		2		2		2	
危険角度(°)	53		53		53		53		60	
フック種類	24t		24t		24t		24t		24t	
フック質量(t)	0.88		0.88		0.88		0.88		0.88	

SD性能

45.5mブーム+2m+10mスーパーラフィングジブ

オフセット	5°		15°		30°		45°		60°	
作業半径 (m)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)
11.0	79.4	24.0								
12.0	78.5	24.0								
14.0	76.8	24.0	78.3	24.0						
16.0	75.0	24.0	76.6	24.0	78.6	24.0				
18.0	72.9	20.0	74.5	21.1	76.6	22.1	78.0	19.8	78.8	18.6
20.0	70.7	15.9	72.2	16.9	74.3	18.2	75.8	18.5	76.5	17.5
22.0	68.4	12.7	70.0	13.5	72.0	14.6	73.5	15.5	74.2	15.9
24.0	66.2	10.1	67.7	10.8	69.6	11.8	71.0	12.5	71.6	12.9
26.0	63.8	7.9	65.4	8.6	67.3	9.5	68.5	10.0	69.0	10.3
28.0	61.4	5.6	63.0	6.4	64.8	7.5	66.0	8.0	66.4	8.2
30.0			60.5	4.4	62.2	5.3	63.3	5.9	63.6	6.1
32.0							60.6	3.9		
掛数	2		2		2		2		2	
危険角度(°)	58		58		58		58		60	
フック種類	24t		24t		24t		24t		24t	
フック質量(t)	0.88		0.88		0.88		0.88		0.88	

SD性能

50.0mブーム+2m+10mスーパーラフィングジブ

オフセット	5°		15°		30°		45°		60°	
作業半径 (m)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)
12.0	79.5	20.0								
14.0	77.9	20.0	79.4	20.0						
16.0	76.4	20.0	77.8	20.0	79.7	20.0				
18.0	74.7	19.9	76.2	20.0	78.0	20.0	79.4	19.6		
20.0	72.7	15.8	74.2	16.8	76.2	18.1	77.5	18.0	78.2	17.1
22.0	70.7	12.6	72.1	13.5	74.0	14.6	75.4	15.5	76.2	15.9
24.0	68.5	10.0	70.0	10.8	71.9	11.8	73.2	12.5	73.8	12.9
26.0	66.5	7.8	67.9	8.6	69.7	9.4	70.9	10.1	71.5	10.4
28.0	64.2	5.5	65.7	6.4	67.4	7.5	68.6	8.0	69.0	8.3
30.0					65.1	5.3	66.2	5.9	66.6	6.2
掛数	2		2		2		2		2	
危険角度(°)	62		62		62		62		63	
フック種類	24t		24t		24t		24t		24t	
フック質量(t)	0.88		0.88		0.88		0.88		0.88	

SD性能

40.9mブーム+2m+15mスーパーラフィングジブ

オフセット 作業半径 (m)	5°		15°		30°		45°		60°	
	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)
11.0	79.3	12.0								
12.0	78.3	12.0								
14.0	76.5	12.0	78.9	12.0						
16.0	74.6	12.0	77.0	12.0						
18.0	72.7	12.0	75.1	12.0	78.3	12.0				
20.0	70.8	12.0	73.2	12.0	76.3	12.0	78.8	12.0		
22.0	68.8	12.0	71.2	12.0	74.3	12.0	76.7	12.0	78.2	12.0
24.0	66.8	11.8	69.2	12.0	72.2	12.0	74.4	12.0	75.9	12.0
26.0	64.5	9.6	66.9	10.6	70.0	11.9	72.2	12.0	73.4	12.0
28.0	62.2	7.8	64.5	8.7	67.5	9.8	69.7	10.6	70.8	11.1
30.0	59.8	5.9	62.2	7.0	65.0	8.0	67.0	8.7	67.9	9.1
32.0	57.3	4.1	59.6	5.1	62.4	6.4	64.3	7.1	64.9	7.4
34.0	54.8	2.6	57.0	3.5	59.7	4.6	61.5	5.4		
36.0					56.9	3.1	58.5	3.7		
38.0							55.3	2.2		
掛数	1		1		1		1		1	
危険角度(°)	52		53		53		53		60	
フック種類	12t		12t		12t		12t		12t	
フック質量(t)	0.42		0.42		0.42		0.42		0.42	

SD性能

45.5mブーム+2m+15mスーパーラフィングジブ

オフセット 作業半径 (m)	5°		15°		30°		45°		60°	
	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)
14.0	77.8	12.0								
16.0	76.1	12.0	78.4	12.0						
18.0	74.4	12.0	76.6	12.0						
20.0	72.8	12.0	74.9	12.0	77.8	12.0				
22.0	71.0	12.0	73.2	12.0	76.0	12.0	78.2	12.0		
24.0	69.2	11.7	71.4	12.0	74.2	12.0	76.2	12.0	77.6	12.0
26.0	67.2	9.5	69.3	10.5	72.2	11.8	74.2	12.0	75.4	11.7
28.0	65.0	7.7	67.2	8.6	70.0	9.7	72.1	10.6	73.1	11.2
30.0	62.8	5.7	65.0	6.8	67.7	8.0	69.7	8.7	70.6	9.2
32.0	60.5	3.9	62.7	5.0	65.5	6.3	67.2	7.1	68.0	7.5
34.0			60.4	3.4	63.0	4.6	64.7	5.4	65.3	5.8
36.0					60.5	3.0	62.1	3.8	62.5	4.0
掛数	1		1		1		1		1	
危険角度(°)	57		58		58		58		60	
フック種類	12t		12t		12t		12t		12t	
フック質量(t)	0.42		0.42		0.42		0.42		0.42	

SD性能

50.0mブーム+2m+15mスーパーラフィングジブ

オフセット 作業半径 (m)	5°		15°		30°		45°		60°	
	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)
14.0	78.9	12.0								
16.0	77.4	12.0	79.4	12.0						
18.0	76.0	12.0	78.0	12.0						
20.0	74.5	12.0	76.4	12.0	79.1	12.0				
22.0	72.9	12.0	74.9	12.0	77.5	12.0	79.6	12.0		
24.0	71.3	11.6	73.3	12.0	75.9	12.0	77.8	12.0	79.1	12.0
26.0	69.3	9.4	71.5	10.4	74.1	11.8	76.1	12.0	77.1	11.5
28.0	67.4	7.5	69.4	8.5	72.2	9.7	74.1	10.6	75.2	10.9
30.0	65.3	5.5	67.4	6.7	70.1	7.9	71.9	8.8	72.9	9.2
32.0	63.2	3.8	65.3	4.9	67.9	6.3	69.8	7.1	70.6	7.5
34.0					65.7	4.5	67.5	5.5	68.2	5.9
36.0							65.0	3.8	65.6	4.1
掛数	1		1		1		1		1	
危険角度(°)	61		62		62		62		62	
フック種類	12t		12t		12t		12t		12t	
フック質量(t)	0.42		0.42		0.42		0.42		0.42	

SD性能

40.9mブーム+2m+19mスーパーラフィングジブ

オフセット	5°		15°		30°		45°		60°	
作業半径 (m)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)
12.0	79.5	12.0								
14.0	77.8	12.0								
16.0	76.1	12.0	79.0	12.0						
18.0	74.4	12.0	77.3	12.0						
20.0	72.7	12.0	75.5	12.0	79.4	12.0				
22.0	70.9	12.0	73.7	12.0	77.4	12.0				
24.0	69.1	12.0	71.8	12.0	75.5	12.0	78.4	10.4		
26.0	67.0	10.5	69.9	11.7	73.6	11.6	76.2	10.2	78.0	9.1
28.0	64.8	8.7	67.7	9.8	71.5	11.1	74.0	9.9	75.7	9.0
30.0	62.7	7.1	65.5	8.1	69.2	9.4	71.8	9.7	73.2	8.9
32.0	60.4	5.4	63.2	6.6	66.8	7.8	69.4	8.7	70.7	8.8
34.0	58.1	3.9	60.9	5.0	64.3	6.4	66.8	7.2	67.8	7.6
36.0	55.6	2.5	58.4	3.6	61.8	4.9	64.2	5.9	64.9	6.2
38.0					59.2	3.5	61.3	4.3		
40.0					56.5	2.2	58.3	2.9		
掛数	1		1		1		1		1	
危険角度(°)	53		54		54		54		60	
フック種類	12t		12t		12t		12t		12t	
フック質量(t)	0.42		0.42		0.42		0.42		0.42	

SD性能

45.5mブーム+2m+19mスーパーラフィングジブ

オフセット	5°		15°		30°		45°		60°	
作業半径 (m)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)
14.0	79.0	12.0								
16.0	77.4	12.0								
18.0	75.9	12.0	78.5	12.0						
20.0	74.3	12.0	77.0	12.0						
22.0	72.8	12.0	75.3	12.0	78.9	12.0				
24.0	71.1	12.0	73.7	12.0	77.1	12.0	79.7	10.6		
26.0	69.2	10.4	72.0	11.6	75.4	11.9	77.9	10.3	79.5	9.2
28.0	67.3	8.5	69.9	9.6	73.5	11.1	76.0	10.1	77.4	9.1
30.0	65.3	6.9	68.0	8.0	71.4	9.3	74.0	9.6	75.3	9.0
32.0	63.2	5.1	65.9	6.4	69.3	7.7	71.8	8.7	73.0	8.6
34.0	61.1	3.6	63.7	4.8	67.1	6.4	69.4	7.2	70.6	7.7
36.0			61.5	3.4	64.7	4.8	67.0	5.9	68.0	6.3
38.0					62.4	3.4	64.6	4.3	65.3	4.7
40.0							62.0	2.9	62.5	3.2
掛数	1		1		1		1		1	
危険角度(°)	58		59		59		59		60	
フック種類	12t		12t		12t		12t		12t	
フック質量(t)	0.42		0.42		0.42		0.42		0.42	

SD性能

50.0mブーム+2m+19mスーパーラフィングジブ

オフセット	5°		15°		30°		45°		60°	
作業半径 (m)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)
16.0	78.6	12.0								
18.0	77.2	12.0	79.7	12.0						
20.0	75.8	12.0	78.3	12.0						
22.0	74.4	12.0	76.8	12.0	80.2	12.0				
24.0	73.0	12.0	75.4	12.0	78.6	12.0				
26.0	71.2	10.2	73.8	11.5	77.1	11.9	79.3	10.4		
28.0	69.4	8.4	72.0	9.5	75.3	11.0	77.6	10.0	78.9	9.1
30.0	67.5	6.7	70.0	7.8	73.4	9.2	75.7	9.4	77.0	8.9
32.0	65.6	4.9	68.1	6.3	71.4	7.7	73.8	8.7	75.0	8.4
34.0			66.1	4.6	69.3	6.3	71.7	7.2	72.9	7.7
36.0			64.1	3.2	67.3	4.7	69.5	5.9	70.6	6.3
38.0					65.1	3.3	67.2	4.3	68.2	4.8
40.0									65.6	3.3
掛数	1		1		1		1		1	
危険角度(°)	62		62		63		63		63	
フック種類	12t		12t		12t		12t		12t	
フック質量(t)	0.42		0.42		0.42		0.42		0.42	

SD性能

40.9mブーム+2m+23mスーパーラフィングジブ

オフセット 作業半径 (m)	5°		15°		30°		45°		60°	
	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)
14.0	79.1	12.0								
16.0	77.5	12.0								
18.0	75.9	12.0	79.2	12.0						
20.0	74.3	12.0	77.6	12.0						
22.0	72.7	12.0	76.0	12.0	80.2	10.4				
24.0	71.0	12.0	74.2	11.5	78.4	10.1				
26.0	69.2	11.3	72.4	10.9	76.5	9.8	79.9	8.1		
28.0	67.2	9.5	70.5	10.3	74.6	9.4	77.8	7.8		
30.0	65.2	7.9	68.5	9.0	72.6	9.0	75.7	7.6	77.9	6.8
32.0	63.1	6.5	66.4	7.6	70.6	8.7	73.6	7.5	75.5	6.7
34.0	61.0	4.9	64.2	6.3	68.5	7.6	71.4	7.3	73.1	6.7
36.0	58.7	3.6	62.0	4.8	66.2	6.3	69.2	7.1	70.5	6.6
38.0	56.4	2.4	59.7	3.5	63.8	5.1	66.6	6.1	67.9	6.5
40.0			57.3	2.4	61.2	3.8	64.0	4.8	65.0	5.3
42.0					58.7	2.6	61.2	3.5		
44.0							58.3	2.2		
掛数	1		1		1		1		1	
危険角度(°)	54		55		55		55		60	
フック種類	12t		12t		12t		12t		12t	
フック質量(t)	0.42		0.42		0.42		0.42		0.42	

SD性能

45.5mブーム+2m+23mスーパーラフィングジブ

オフセット 作業半径 (m)	5°		15°		30°		45°		60°	
	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)
16.0	78.7	12.0								
18.0	77.2	12.0								
20.0	75.8	12.0	78.9	12.0						
22.0	74.3	12.0	77.4	12.0						
24.0	72.9	12.0	75.9	12.0	79.7	10.2				
26.0	71.2	11.1	74.2	11.3	78.0	9.9				
28.0	69.3	9.3	72.5	10.6	76.3	9.6	79.2	7.9		
30.0	67.5	7.7	70.6	8.9	74.6	9.3	77.4	7.7	79.3	6.9
32.0	65.6	6.2	68.7	7.4	72.7	8.9	75.5	7.6	77.2	6.8
34.0	63.5	4.6	66.7	6.1	70.7	7.5	73.5	7.4	75.1	6.7
36.0	61.5	3.3	64.6	4.6	68.6	6.3	71.6	7.2	72.9	6.6
38.0			62.5	3.3	66.4	4.9	69.3	6.0	70.6	6.5
40.0					64.2	3.6	66.9	4.8	68.1	5.4
42.0							64.4	3.4	65.3	3.9
44.0									62.5	2.6
掛数	1		1		1		1		1	
危険角度(°)	59		59		60		60		60	
フック種類	12t		12t		12t		12t		12t	
フック質量(t)	0.42		0.42		0.42		0.42		0.42	

SD性能

50.0mブーム+2m+23mスーパーラフィングジブ

オフセット 作業半径 (m)	5°		15°		30°		45°		60°	
	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)
16.0	79.6	11.0								
18.0	78.3	11.0								
20.0	77.0	11.0	79.8	11.0						
22.0	75.7	11.0	78.5	11.0						
24.0	74.4	11.0	77.2	11.0						
26.0	73.0	10.9	75.8	11.0	79.3	10.1				
28.0	71.3	9.1	74.3	10.4	77.8	9.8				
30.0	69.5	7.5	72.5	8.7	76.3	9.4	78.8	7.8		
32.0	67.7	5.9	70.7	7.3	74.6	8.7	77.1	7.7	78.7	6.8
34.0	65.8	4.4	68.9	5.9	72.7	7.4	75.4	7.5	76.9	6.7
36.0			66.9	4.4	70.7	6.2	73.5	7.0	74.9	6.7
38.0					68.7	4.8	71.4	6.0	72.8	6.4
40.0					66.7	3.5	69.3	4.7	70.6	5.4
42.0							67.0	3.4	68.1	4.0
掛数	1		1		1		1		1	
危険角度(°)	63		63		64		64		64	
フック種類	12t		12t		12t		12t		12t	
フック質量(t)	0.42		0.42		0.42		0.42		0.42	

SD性能

40.9mブーム+2m+27mスーパーラフィングジブ

オフセット 作業半径 (m)	5°		15°		30°		45°		60°	
	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)
14.0	80.3	12.0								
16.0	78.9	12.0								
18.0	77.4	12.0								
20.0	75.9	12.0	79.5	11.2						
22.0	74.4	12.0	77.9	10.7						
24.0	72.8	11.4	76.2	10.2						
26.0	71.1	10.6	74.5	9.6	79.2	7.9				
28.0	69.4	9.9	72.8	9.1	77.4	7.6				
30.0	67.6	8.6	71.1	8.6	75.7	7.4	79.4	6.3		
32.0	65.6	7.2	69.3	8.1	73.8	7.2	77.4	6.1	80.0	5.4
34.0	63.6	5.9	67.4	7.1	71.9	7.0	75.4	6.0	77.7	5.3
36.0	61.5	4.5	65.3	6.0	70.0	6.8	73.3	5.8	75.4	5.2
38.0	59.4	3.3	63.1	4.7	67.9	6.2	71.1	5.7	73.0	5.2
40.0	57.3	2.3	60.9	3.5	65.6	5.2	68.9	5.5	70.4	5.1
42.0			58.7	2.4	63.3	4.0	66.5	5.1	67.9	5.1
44.0					60.8	2.9	63.9	3.9	65.0	4.4
46.0					58.3	1.9	61.1	2.8		
48.0							58.2	1.7		
掛数	1		1		1		1		1	
危険角度(°)	55		56		56		56		60	
フック種類	12t		12t		12t		12t		12t	
フック質量(t)	0.42		0.42		0.42		0.42		0.42	

SD性能

45.5mブーム+2m+27mスーパーラフィングジブ

オフセット 作業半径 (m)	5°		15°		30°		45°		60°	
	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)
16.0	79.8	11.0								
18.0	78.4	11.0								
20.0	77.1	11.0	80.5	11.0						
22.0	75.7	11.0	79.2	10.9						
24.0	74.3	11.0	77.6	10.4						
26.0	73.0	11.0	76.2	10.0	80.3	8.0				
28.0	71.3	9.9	74.6	9.4	78.8	7.8				
30.0	69.5	8.3	73.0	8.9	77.1	7.5				
32.0	67.8	7.0	71.3	8.2	75.5	7.3	78.8	6.2		
34.0	65.8	5.6	69.5	6.9	73.8	7.1	76.9	6.0	79.2	5.3
36.0	64.0	4.2	67.6	5.7	72.1	7.0	75.2	5.9	77.1	5.3
38.0	62.0	3.0	65.6	4.4	70.1	6.1	73.3	5.8	75.0	5.2
40.0			63.5	3.2	68.1	5.0	71.3	5.6	72.8	5.1
42.0					65.9	3.8	69.2	5.1	70.6	5.1
44.0					63.7	2.7	66.8	3.9	68.0	4.5
46.0							64.3	2.7	65.3	3.2
掛数	1		1		1		1		1	
危険角度(°)	60		60		61		61		61	
フック種類	12t		12t		12t		12t		12t	
フック質量(t)	0.42		0.42		0.42		0.42		0.42	

SD性能

50.0mブーム+2m+27mスーパーラフィングジブ

オフセット 作業半径 (m)	5°		15°		30°		45°		60°	
	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)
18.0	79.1	9.0								
20.0	77.9	9.0								
22.0	76.7	9.0	79.9	9.0						
24.0	75.4	9.0	78.6	9.0						
26.0	74.1	9.0	77.3	9.0						
28.0	72.9	9.0	76.0	9.0	80.0	7.9				
30.0	71.4	8.1	74.7	8.9	78.5	7.6				
32.0	69.7	6.8	73.1	8.1	77.0	7.4	80.1	6.3		
34.0	67.9	5.3	71.3	6.8	75.5	7.3	78.4	6.1		
36.0	66.1	3.9	69.6	5.5	73.9	7.0	76.8	6.0	78.6	5.3
38.0			67.7	4.2	72.1	6.0	75.0	5.8	76.7	5.2
40.0					70.2	4.9	73.3	5.7	74.8	5.2
42.0					68.2	3.7	71.3	5.0	72.8	5.1
44.0					66.1	2.6	69.1	3.8	70.6	4.6
46.0									68.1	3.3
掛数	1		1		1		1		1	
危険角度(°)	63		64		64		65		65	
フック種類	12t		12t		12t		12t		12t	
フック質量(t)	0.42		0.42		0.42		0.42		0.42	

SD性能

40.9mブーム+2m+31mスーパーラフィングジブ

オフセット 作業半径 (m)	5°		15°		30°		45°		60°	
	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)
16.0	79.7	9.0								
18.0	78.3	9.0								
20.0	76.9	9.0								
22.0	75.5	9.0	79.6	9.0						
24.0	74.1	9.0	78.1	8.7						
26.0	72.7	9.0	76.5	8.3						
28.0	71.2	8.9	74.9	8.0	80.0	6.4				
30.0	69.6	8.3	73.3	7.6	78.4	6.2				
32.0	67.9	7.8	71.7	7.3	76.7	6.1				
34.0	66.1	6.6	70.0	6.9	74.9	5.9	79.0	4.9		
36.0	64.1	5.4	68.3	6.6	73.2	5.7	77.0	4.8		
38.0	62.1	4.2	66.3	5.7	71.2	5.5	75.1	4.7	77.7	4.2
40.0	60.1	3.1	64.2	4.5	69.4	5.3	73.1	4.6	75.4	4.2
42.0	58.0	2.1	62.1	3.4	67.5	5.1	70.9	4.5	73.0	4.1
44.0			59.9	2.5	65.2	4.1	68.8	4.4	70.5	4.1
46.0					62.9	3.1	66.5	4.3	67.8	4.0
48.0					60.4	2.1	63.8	3.2	64.9	3.8
50.0							61.0	2.2		
掛数	1		1		1		1		1	
危険角度(°)	56		57		57		57		60	
フック種類	12t		12t		12t		12t		12t	
フック質量(t)	0.42		0.42		0.42		0.42		0.42	

SD性能

45.5mブーム+2m+31mスーパーラフィングジブ

オフセット 作業半径 (m)	5°		15°		30°		45°		60°	
	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)
18.0	79.3	9.0								
20.0	78.0	9.0								
22.0	76.8	9.0	80.6	9.0						
24.0	75.5	9.0	79.3	9.0						
26.0	74.2	9.0	77.8	8.5						
28.0	72.9	9.0	76.4	8.2						
30.0	71.5	8.8	74.9	7.8	79.6	6.3				
32.0	69.8	7.6	73.5	7.5	78.0	6.1				
34.0	68.1	6.4	72.0	7.2	76.4	6.0	80.2	5.0		
36.0	66.2	5.0	70.3	6.5	74.9	5.8	78.5	4.9		
38.0	64.4	3.8	68.4	5.4	73.2	5.6	76.6	4.7	79.1	4.2
40.0	62.5	2.7	66.4	4.2	71.5	5.4	74.8	4.6	77.1	4.2
42.0			64.5	3.1	69.7	5.0	72.9	4.5	75.0	4.1
44.0					67.6	3.9	71.1	4.5	72.7	4.1
46.0					65.5	2.9	69.1	4.2	70.5	4.0
48.0							66.6	3.1	68.1	3.8
50.0							64.2	2.2	65.3	2.7
掛数	1		1		1		1		1	
危険角度(°)	60		61		62		62		62	
フック種類	12t		12t		12t		12t		12t	
フック質量(t)	0.42		0.42		0.42		0.42		0.42	

SD性能

50.0mブーム+2m+31mスーパーラフィングジブ

オフセット 作業半径 (m)	5°		15°		30°		45°		60°	
	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)	ブーム角 (°)	荷重 (ton)
18.0	80.0	8.0								
20.0	78.8	8.0								
22.0	77.7	8.0								
24.0	76.6	8.0	80.1	8.0						
26.0	75.4	8.0	78.9	8.0						
28.0	74.1	8.0	77.7	8.0						
30.0	72.9	8.0	76.5	8.0	80.6	6.4				
32.0	71.5	7.3	75.0	7.7	79.3	6.2				
34.0	69.9	6.1	73.7	7.4	77.8	6.1				
36.0	68.2	4.7	72.0	6.3	76.4	5.9	79.7	4.9		
38.0	66.4	3.5	70.3	5.2	74.8	5.7	78.1	4.8		
40.0			68.5	4.0	73.4	5.5	76.5	4.7	78.6	4.2
42.0			66.6	2.9	71.6	4.9	74.8	4.6	76.7	4.1
44.0					69.7	3.8	73.1	4.5	74.8	4.1
46.0					67.7	2.7	71.2	4.1	72.8	4.1
48.0							69.0	3.1	70.6	3.8
50.0									68.2	2.7
掛数	1		1		1		1		1	
危険角度(°)	64		64		65		65		65	
フック種類	12t		12t		12t		12t		12t	
フック質量(t)	0.42		0.42		0.42		0.42		0.42	